

AI 0,75- 8 GY-GB - Ferrule

1208979

<https://www.phoenixcontact.com/us/products/1208979>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, sleeve length: 8 mm, color: gray

Your advantages

- Due to the increased diameter of the insulating collar, this type of ferrule is specifically used with AWG cables
- These ferrules enable practical crimping of conductors with increased insulation

Commercial data

Item number	1208979
Packing unit	500 pc
Minimum order quantity	500 pc
Sales key	BH34
Product key	BH341S
Catalog page	Page 484 (C-3-2019)
GTIN	4046356130394
Weight per piece (including packing)	0.097 g
Weight per piece (excluding packing)	0.069 g
Customs tariff number	85369010
Country of origin	DE

AI 0,75- 8 GY-GB - Ferrule

1208979

<https://www.phoenixcontact.com/us/products/1208979>



Technical data

Product properties

Product type	Cable end sleeve
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M

Data management status


Article revision	06
------------------	----

Connection data

Conductor connection

Conductor cross section flexible max.	0.75 mm ²
Conductor cross section AWG max.	18
Stripping length	11 mm

Dimensions

Dimensional drawing	
Sleeve length	8 mm
Maximum stripping length	11 mm
Ferrule diameter	1.3 mm
Sleeve wall thickness	0.15 mm
Insulating collar thickness	0.25 mm
Inner dimensions of the insulating collar	3.4 mm

Material specifications

Color	gray (RAL 7042)
Material	CU-DHP
Flammability rating according to UL 94	HB
Coating	tin-plated (galvanic)
Components	free from silicone and halogen

Mechanical properties

Technical data

Sleeve length	8 mm
---------------	------

Environmental and real-life conditions

Ambient conditions

Permanent temperature	105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature	120 °C

AI 0,75- 8 GY-GB - Ferrule

1208979

<https://www.phoenixcontact.com/us/products/1208979>



Standards and regulations

Design according to standard

Color code in accordance with DIN 46228-4, UL 486F-E

AI 0,75- 8 GY-GB - Ferrule


1208979

<https://www.phoenixcontact.com/us/products/1208979>



Drawings

Dimensional drawing



Length (b), sleeve length (h), insulating collar inner dimension (d), sleeve diameter (k), insulating collar thickness (i), sleeve wall thickness (j)

AI 0,75- 8 GY-GB - Ferrule

1208979

<https://www.phoenixcontact.com/us/products/1208979>



Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1208979>



cULus Listed

Approval ID: E488001

AI 0,75- 8 GY-GB - Ferrule

1208979

<https://www.phoenixcontact.com/us/products/1208979>



Classifications

ECLASS

ECLASS-11.0	27400201
ECLASS-13.0	27400201
ECLASS-12.0	27400201

ETIM

ETIM 9.0	EC000005
----------	----------

UNSPSC

UNSPSC 21.0	27121700
-------------	----------

AI 0,75- 8 GY-GB - Ferrule

1208979

<https://www.phoenixcontact.com/us/products/1208979>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com