

RF-12P1N8A80DU - Cable connector



1607228

<https://www.phoenixcontact.com/pc/products/1607228>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight, Screw locking mechanism, M23, number of positions: 12, contact connection type: Pin, shielded: yes, degree of protection: IP67, cable diameter range: 5 mm ... 13.2 mm, number of positions: 12, connection method: Crimp connection, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242243

Commercial data

Item number	1607228
Packing unit	20 pc
Minimum order quantity	20 pc
Product key	ABRAGA
Catalog page	Page 78 (PC-2011)
GTIN	4046356174756
Weight per piece (including packing)	100.495 g
Weight per piece (excluding packing)	50.41 g
Customs tariff number	85366990
Country of origin	DE

RF-12P1N8A80DU - Cable connector



1607228

<https://www.phoenixcontact.com/pc/products/1607228>

Technical data

Notes

General	Order crimp contacts Ø 1 mm separately
---------	--

Mounting

Connection method	Crimp connection
-------------------	------------------

Product properties

Product type	Circular connector (cable-side)
Number of positions	12
Connection profile	12
Application	Feedback, signal Signal
Series	RF
Shielded	yes
Coding	N
Thread type	M23

Material specifications

Seal material	FPM
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM
Housing material	Metal

Connection data

Conductor connection	
Connection method	Crimp connection

Electrical properties

Contact	
Contact diameter	1 mm
Max. current	8 A
Nominal voltage U_N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connector

Type	straight
Direction of rotation	Standard

RF-12P1N8A80DU - Cable connector



1607228

<https://www.phoenixcontact.com/pc/products/1607228>

Cable/line

External cable diameter	5 mm ... 13.2 mm
-------------------------	------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	2000 m

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com