

PRODUCT-DETAILS

AUP-R T4-T5-T6 CON.WITHDRAW.SIG.

AUP-R T4-T5-T6 CON.WITHDRAW.SIG.



General Information

| | |
|-----------------------|---|
| Extended Product Type | AUP-R T4-T5-T6 CON.WITHDRAW.SIG. |
| Product ID | 1SDA054919R1 |
| EAN | 8015644557034 |
| Catalog Description | AUP-R T4-T5-T6 CON.WITHDRAW.SIG. |
| Long Description | 1 POSITION CONTACT C.BREAKERS WITHDRAWABLE T4-T5-T6 |

Ordering

| | |
|------------------------|---------------|
| EAN | 8015644557034 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

Dimensions

| | |
|--------------------|---------|
| Product Net Weight | 0.03 kg |
|--------------------|---------|

Container Information

| | |
|-------------------------|---------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 110 mm |
| Package Level 1 Height | 60 mm |
| Package Level 1 Depth / | 140 mm |

| | |
|------------------------------|---------------|
| Length | |
| Package Level 1 Gross Weight | 0.023 kg |
| Package Level 1 EAN | 8015644557034 |

Additional Information

| | |
|--|------------------------|
| Configuration Type | Loose or configurable |
| Number of Auxiliary Contacts CO (SPDT) | 1 |
| Product Main Type | Accessories for Tmax T |
| Product Name | Accessory |
| Product Type | ACC |
| Standards | IEC |
| Suitable For | T4, T5, T6 |
| Suitable for Product Class | SACE Tmax T |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210023D0201 |
| Declaration of Conformity - CE | 1SDL000165R0001 |
| Instructions and Manuals | 1SDC210033D0202 |

Classifications

| | |
|----------------------------|--|
| ETIM 6 | EC000041 - Auxiliary contact block |
| ETIM 7 | EC000041 - Auxiliary contact block |
| Object Classification Code | Q |
| UNSPSC | 39120000 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax T

