

PRODUCT-DETAILS

OBOC5000-24VDC

OBOC5000-24VDC Optocoupler R600 A1-A2=24VDC,4.5-58VDC/ 1 mA-5 A,MOSFET



General Information

Extended Product Type	OBOC5000-24VDC
Product ID	1SNA645024R2100
EAN	4013614507915
Catalog Description	OBOC5000-24VDC Optocoupler R600 A1-A2=24VDC,4.5-58VDC/ 1 mA-5 A,MOSFET
Long Description	Screw optocoupler OBOC5000-24VDC: 24VDC Rated control supply voltage/ solid-state output rated 4.5-58VDC, 1 mA up to 5 A with integrated LED

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85369095

Popular Downloads

Instructions and Manuals	1SVC645000M9000
--------------------------	-----------------

Dimensions

Product Net Width	6 mm
Product Net Height	67.5 mm
Product Net Depth / Length	70 mm

Product Net Weight	0.02 kg
--------------------	---------

Technical

Function	Boxed optocoupler R600
Output	solid-state output
Output Signal	4.5 ... 58VDC / 1 mA ... 5 A
Rated Control Supply Voltage (U _s)	24 V DC
Terminal Type	Screw Terminals

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2017010303938926
CSA Certificate	CSA_254821
cUR Certificate	cUR_E352056
Declaration of Conformity - CE	1SVD982016-0001
EAC Certificate	EAC_RU_C-FR.ME77.B.01634
Instructions and Manuals	1SVC645000M9000
LR Certificate	LR_16_20068
RoHS Information	1SVD982016-0001
UR Certificate	UR_E352056

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	73 mm
Package Level 1 Height	71 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Gross Weight	0.23 kg
Package Level 1 EAN	3472596450243

Classifications

Object Classification Code	K
ETIM 4	EC001504 - Optocoupler
ETIM 5	EC001504 - Optocoupler
ETIM 6	EC001504 - Optocoupler
ETIM 7	EC001504 - Optocoupler
eClass	7.0 27371604
UNSPSC	32111705
E-Number (Sweden)	4029176

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

