

PRODUCT-DETAILS

CR-P024AC2

CR-P024AC2 Pluggable interface relay 2c/o, A1-A2=24VAC, 250V/8A



General Information

| | |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CR-P024AC2 |
| Product ID | 1SVR405601R0000 |
| EAN | 4013614498220 |
| Catalog Description | CR-P024AC2 Pluggable interface relay 2c/o, A1-A2=24VAC, 250V/8A |
| Long Description | The CR-P024AC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 24 V AC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC117001D0203 |
| Instructions and Manuals | 1SVC405600M9000 |

Dimensions

| | |
|-------------------|---------|
| Product Net Width | 12.7 mm |
|-------------------|---------|

| | |
|----------------------------|----------|
| Product Net Height | 15.7 mm |
| Product Net Depth / Length | 29 mm |
| Product Net Weight | 0.014 kg |

Technical

| | |
|------------------------------------------------|------------------------------------|
| Function | Pluggable pcb interface relay CR-P |
| Sub-Function | Relay w/o built in LED |
| Output | 2 c/o (SPDT) contacts |
| Output Signal | 250 V / 8 A |
| Rated Control Supply Voltage (U _s) | 24 V AC |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------------------|
| CCC Certificate | CCC_2007010303228779 |
| CSA Certificate | CSA_1587291 |
| cUR Certificate | cUR_E244330 |
| Declaration of Conformity - CE | No declaration needed |
| EAC Certificate | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information | 1SAA981009-2401 |
| Instructions and Manuals | 1SVC405600M9000 |
| RMRS Certificate | RMRS_1740019250 |
| RoHS Information | 1SVD981001-4400 |
| UR Certificate | UR_E244330 |
| VDE Certificate | VDE_40019129 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 10 piece |
| Package Level 1 Width | 332 mm |
| Package Level 1 Height | 28 mm |
| Package Level 1 Depth / Length | 17 mm |
| Package Level 1 Gross Weight | 0.157 kg |
| Package Level 1 EAN | 4013614372995 |

Classifications

| | |
|----------------------------|----------------------------|
| Object Classification Code | K |
| ETIM 4 | EC001437 - Switching relay |
| ETIM 5 | EC001437 - Switching relay |
| ETIM 6 | EC001437 - Switching relay |
| ETIM 7 | EC001437 - Switching relay |
| eClass | 7.0 27371601 |
| UNSPSC | 39122331 |

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

