

CABLE-FLK14/OE/0,14/ 600 - Cable



2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Round cable set; connection 1: Single wires (14-position) (The wires are marked and fitted with ferrules); connection 2: IDC/FLK socket strip (1x 14-position); cable length: 6 m



Your advantages

- 14 pos.
- Connector in accordance with IEC 60603-13
- 1:1 connection
- Open end at one end

Commercial data

Item number	2305787
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	CK2213
Catalog page	Page 562 (C-5-2019)
GTIN	4046356039123
Weight per piece (including packing)	367.6 g
Weight per piece (excluding packing)	355.2 g
Customs tariff number	85444290
Country of origin	DE

CABLE-FLK14/OE/0,14/ 600 - Cable



2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Technical data

Product properties

Product type	System cable
--------------	--------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Nominal operating mode	100% operating factor
Current (Per path, 50°C)	≤ 1 A (Uncoiled, see derating)
Current (Per path, 70°C)	≤ 0.6 A (Uncoiled, see derating)

Cable/line

Cable length	6 m
--------------	-----

14X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	14
Shielded	no
Cable type	14X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	14x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.40 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	55 mm
Smallest bending radius, movable installation	104 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)

CABLE-FLK14/OE/0,14/ 600 - Cable




2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
IDC/FLK14 (1)	() = black
IDC/FLK14 (2)	() = brown
IDC/FLK14 (3)	() = red
IDC/FLK14 (4)	() = orange
IDC/FLK14 (5)	() = yellow
IDC/FLK14 (6)	() = green
IDC/FLK14 (7)	() = blue
IDC/FLK14 (8)	() = violet
IDC/FLK14 (9)	() = gray
IDC/FLK14 (10)	() = white
IDC/FLK14 (11)	() = white-black
IDC/FLK14 (12)	() = white-brown
IDC/FLK14 (13)	() = white-red
IDC/FLK14 (14)	() = white-orange
Cable type	Cable for one module

Connection data

Connection 1

Connection method	Single wires
Stripping length (Sheath)	≈  mm
Number of positions	14
Note	The wires are marked and fitted with ferrules

Connection 2

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--


CABLE-FLK14/OE/0,14/ 600 - Cable

2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Drawings


Schematic diagram



2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Diagram



Maximum permissible current per path in uncoiled state

CABLE-FLK14/OE/0,14/ 600 - Cable



2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2305787>



EAC

Approval ID: RU*-DE.HB*35.B00385



UL Listed

Approval ID: FILE E 238705

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	1 A	-	-



cUL Listed

Approval ID: FILE E 238705

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	1 A	-	-

cULus Listed

CABLE-FLK14/OE/0,14/ 600 - Cable



2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Classifications

ECLASS

ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

ETIM

ETIM 9.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

CABLE-FLK14/OE/0,14/ 600 - Cable



2305787

<https://www.phoenixcontact.com/pc/products/2305787>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com