

# BC 35,6 DKL R KMGY - Housing cover

2896157

<https://www.phoenixcontact.com/pc/products/2896157>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

DIN rail housing for use in distribution boards in accordance with DIN 43880, Latching cover (non-detachable), width: 35.6 mm, height: 45 mm, depth: 8 mm, color: light grey (similar RAL 7035)



## Your advantages

- Coordinated housing and connection system for faster device development
- Individual online configuration for diverse applications in building automation
- Variety of connection technology
- Can be mounted on the DIN rail or the wall
- With DIN-rail-mountable bus connector and power connector system as an option
- Tool-free mounting
- Available in overall widths from one to nine HP (17.8 mm ... 161.6 mm)
- Compliant with DIN EN 43880

## Commercial data

Item number	2896157
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	ACHBAB
Catalog page	Page 698 (C-1-2013)
GTIN	4046356096560
Weight per piece (including packing)	5.95 g
Weight per piece (excluding packing)	4.47 g
Customs tariff number	84879090
Country of origin	DE

# BC 35,6 DKL R KMGY - Housing cover



2896157

<https://www.phoenixcontact.com/pc/products/2896157>

## Technical data

### Notes

General	Refer to the data sheet for the range in the download area.
---------	---

### Product properties

Product type	Cover
Product family	BC 35,6
Housing series	BC
Type	Latching cover (non-detachable)
Housing type	DIN rail housing for use in distribution boards in accordance with DIN 43880
Ventilation openings present	no

### Dimensions

Width	35.6 mm
Height	45 mm
Depth	8 mm

### Material specifications

Color (Housing)	light grey (RAL 7035)
Flammability rating according to UL 94	V0
Housing material	Polycarbonate
Surface characteristics	untreated

### Environmental and real-life conditions

#### Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 Hz ... 58.1 Hz)
Acceleration	2g (58.1 Hz ... 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

#### Glow-wire test

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

#### Mechanical strength / tumbling barrel

Specification	IEC 60068-2-31:2008-05
Height of fall	50 cm
Frequency	50

# BC 35,6 DKL R KMGY - Housing cover



2896157

<https://www.phoenixcontact.com/pc/products/2896157>

## Shocks

Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)

## Degree of protection (IP code)

Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
---------------	---

## Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Relative humidity (storage/transport)	95 %

## Mounting

Mounting type	Latching with upper housing part
Mounting position	Vertical (horizontal DIN rail)

# BC 35,6 DKL R KMGY - Housing cover



2896157

<https://www.phoenixcontact.com/pc/products/2896157>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2896157>



**UL Recognized**

Approval ID: FILE E 240868

# BC 35,6 DKL R KMGY - Housing cover



2896157

<https://www.phoenixcontact.com/pc/products/2896157>

## Classifications

### ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190603

### ETIM

ETIM 9.0	EC001031
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

# BC 35,6 DKL R KMGY - Housing cover



2896157

<https://www.phoenixcontact.com/pc/products/2896157>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)