

# EMG 45-DIO 8P-1N5408 - Diode block

2954879

<https://www.phoenixcontact.com/nz/products/2954879>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Diode module, with eight diodes, common cathode, diode type 1N 5408



## Your advantages

- Spark-suppression diodes for limiting surge voltages of inductive loads
- Electrical decoupling of messages in fault reporting systems

## Commercial data

Item number	2954879
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	CK4M11
Product key	CK4M11
Catalog page	Page 266 (C-5-2019)
GTIN	4017918085155
Weight per piece (including packing)	91.58 g
Weight per piece (excluding packing)	91.58 g
Country of origin	DE

# EMG 45-DIO 8P-1N5408 - Diode block



2954879

<https://www.phoenixcontact.com/nz/products/2954879>

## Technical data

### Product properties

Product type	Diode module
--------------	--------------

### Insulation characteristics

Pollution degree	2
------------------	---

### Input data

#### Diode

Description of the input	8 diodes, common cathode
Diode type	1 N 5408
Max. operating voltage $U_{max}$	250 V AC
Peak reverse voltage per diode	1000 V
Reverse current per diode	10 $\mu$ A
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	1.5 A (with single load) 0.3 A (with simultaneous loads)

### Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Dimensions

Width	45 mm
Height	75 mm
Depth	55 mm

### Material specifications

Color	green (RAL 6021)
-------	------------------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Approvals

#### CE

Certificate	CE-compliant
-------------	--------------

# EMG 45-DIO 8P-1N5408 - Diode block



2954879

<https://www.phoenixcontact.com/nz/products/2954879>

Note	and EN 61326
------	--------------

## Standards and regulations

Standards/regulations	DIN EN 50178
-----------------------	--------------

## Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

# EMG 45-DIO 8P-1N5408 - Diode block



2954879

<https://www.phoenixcontact.com/nz/products/2954879>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/nz/products/2954879>



**EAC**

Approval ID: RU\*DE\*08.B.01841/19

# EMG 45-DIO 8P-1N5408 - Diode block



2954879

<https://www.phoenixcontact.com/nz/products/2954879>

## Classifications

### ECLASS

ECLASS-11.0	27371010
ECLASS-12.0	27371010
ECLASS-13.0	27371010

### ETIM

ETIM 9.0	EC002278
----------	----------

### UNSPSC

UNSPSC 21.0	32151500
-------------	----------

# EMG 45-DIO 8P-1N5408 - Diode block



2954879

<https://www.phoenixcontact.com/nz/products/2954879>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Unit 15C, 906-930 Great South Road, Penrose

Auckland 1061

0508 474 636

[sales@phoenixcontact.co.nz](mailto:sales@phoenixcontact.co.nz)