

# AB-STI/3 - Support bracket


3030831

<https://www.phoenixcontact.com/pc/products/3030831>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Support bracket, Bracket for busbars, set every 20 cm, pitch: 200 mm, width: 2 mm, height: 52 mm, number of positions: 1, color: blue



## Commercial data

Item number	3030831
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BE2Z1X
Catalog page	Page 288 (C-3-2013)
GTIN	4017918193089
Weight per piece (including packing)	8 g
Weight per piece (excluding packing)	7.421 g
Customs tariff number	39269097
Country of origin	DE

# AB-STI/3 - Support bracket



3030831

<https://www.phoenixcontact.com/pc/products/3030831>

## Technical data

### Product properties

Product type	Support bracket
Number of positions	1
Pitch	200 mm

### Dimensions

Width	2 mm
Height	52 mm
Pitch	200 mm

### Material specifications

Color	blue
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

# AB-STI/3 - Support bracket

3030831

<https://www.phoenixcontact.com/pc/products/3030831>



## Classifications

### ECLASS

ECLASS-11.0

27400607

### ETIM

ETIM 8.0

EC001166

### UNSPSC

UNSPSC 21.0

39121700

# AB-STI/3 - Support bracket

3030831

<https://www.phoenixcontact.com/pc/products/3030831>



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)