

22MM PLASTIC ROUND COMPLETE UNIT COMBINATION: INDICATOR LIGHT WITH SMOOTH LENSE NON-ILLUMINATED WITH LAMP HOLDER BA 9S WITHOUT LAMP SPRING-LOADED TERMINAL WITH HOLDER GREEN !!!  
 Phased-out product !!! SIRIUS ACT 3SU1 is successor Preferred successor type is >>3SU1001-6AA40-0AA0 + 3SU1500-0AA10-0AA0<<

<b>design of the product</b>	Complete unit round
<b>Enclosure</b>	
<b>shape of the enclosure front</b>	round
<b>material of the enclosure</b>	plastic
<b>number of command points</b>	0
<b>Actuator</b>	
<b>design of the actuating element</b>	indicator light
product extension optional light source	Yes
color of the actuating element	green
<b>material of the actuating element</b>	plastic
<b>shape of the actuating element</b>	Smooth lens
<b>number of switching positions</b>	0
<b>Front ring</b>	
<b>product component front ring</b>	No
<b>Holder</b>	
<b>material of the holder</b>	Plastic
<b>Contact block/ lampholder</b>	
<b>socket design</b>	BA 9s without lamp
<b>number of lampholders</b>	1
<b>number of switching elements</b>	0
<b>General technical data</b>	
<b>product function</b>	
• positive opening	No
• EMERGENCY STOP function	No
product component light source	No
<b>protection class IP</b>	IP66
<b>vibration resistance according to IEC 60068-2-6</b>	20 ... 200 Hz: 5g
<b>reference code according to IEC 81346-2</b>	P
<b>Substance Prohibitance (Date)</b>	07/01/2006
<b>Auxiliary circuit</b>	
<b>number of NC contacts for auxiliary contacts</b>	0
<b>number of NO contacts for auxiliary contacts</b>	0
number of CO contacts for auxiliary contacts	0
<b>Connections/ Terminals</b>	
<b>type of electrical connection</b>	spring-loaded terminals
<b>tightening torque of the screws in the bracket</b>	1 ... 1.2 N·m
<b>Ambient conditions</b>	
<b>ambient temperature</b>	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
environmental category during operation according to IEC 60721	3K6
<b>Installation/ mounting/ dimensions</b>	
<b>fastening method</b>	front mounting
<b>shape of the installation opening</b>	round
<b>mounting diameter</b>	22 mm
<b>mounting height</b>	11 mm
<b>installation width</b>	28 mm
<b>installation depth</b>	49 mm

## Accessories

product component holder for 3 switching elements

No

## Certificates/ approvals

General Product Approval

Marine / Shipping



Marine / Shipping

other



[Miscellaneous](#)

[Confirmation](#)

## Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3204-6AA40-0CC0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3204-6AA40-0CC0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3204-6AA40-0CC0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3204-6AA40-0CC0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3204-6AA40-0CC0&lang=en)

last modified:

2/26/2021