



Figure similar

Digital monitoring relay Current monitoring, 22.5 mm from 2-500 mA AC/DC  
Overshoot and undershoot 24 to 240 V AC/DC 50 to 60 Hz DC and AC ON  
delay and noise pulses delay 0.1 to 20 s Hysteresis 0.1 to 250 mA 1  
change-over contact with or without fault buffer spring-type connection  
system

<b>product brand name</b>	SIRIUS
<b>product designation</b>	Current monitoring relay with digital setting
<b>product type designation</b>	3UG4
<b>General technical data</b>	
<b>product function</b>	Current monitoring relay
<b>design of the display</b>	LCD
<b>insulation voltage for overvoltage category III according to IEC 60664</b>	690 V
• with degree of pollution 3 rated value	3
<b>degree of pollution</b>	3
<b>surge voltage resistance rated value</b>	4 kV
<b>maximum permissible voltage for safe isolation</b>	300 V
• between auxiliary and auxiliary circuit	300 V
• between control and auxiliary circuit	IP20
<b>protection class IP</b>	IP20
<b>shock resistance according to IEC 60068-2-27</b>	sinusoidal half-wave 15g / 11 ms
<b>vibration resistance according to IEC 60068-2-6</b>	1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
<b>mechanical service life (operating cycles) typical</b>	10 000 000
<b>electrical endurance (operating cycles) at AC-15 at 230 V typical</b>	100 000
<b>thermal current of the switching element with contacts maximum</b>	5 A
<b>reference code according to IEC 81346-2</b>	K
<b>relative repeat accuracy</b>	1 %
<b>Substance Prohibitance (Date)</b>	05/01/2012
<b>Product Function</b>	
<b>product function</b>	Yes
• overcurrent detection 1 phase	No
• overcurrent detection 3 phase	Yes
• undercurrent detection 1 phase	No
• undercurrent detection 3 phases	Yes
• overcurrent detection DC	Yes
• undercurrent detection DC	Yes
• current window recognition DC	Yes
• voltage window recognition 1 phase	No
• voltage window recognition 3 phase	No
• adjustable open/closed-circuit current principle	Yes
• external reset	Yes
• auto-RESET	Yes
<b>Supply voltage</b>	
<b>type of voltage of the supply voltage</b>	AC/DC

<b>supply voltage 1 at AC</b>	
• at 50 Hz	20.4 ... 264 V
• at 60 Hz	20.4 ... 264 V
<b>supply voltage 1 at DC</b>	20.4 ... 264 V

#### Measuring circuit

<b>type of current for monitoring</b>	AC/DC
<b>measurable current</b>	0.003 ... 0.6 A
<b>measurable line frequency</b>	40 ... 500 Hz
<b>adjustable current response value current</b>	
• 1	0.003 ... 0.5 A
• 2	0.003 ... 0.5 A
<b>adjustable response delay time</b>	
• when starting	0.1 ... 20 s
• with lower or upper limit violation	0.1 ... 20 s
<b>adjustable switching hysteresis for measured current value</b>	0.1 ... 250 mA
<b>buffering time in the event of power failure minimum</b>	10 ms
<b>accuracy of digital display</b>	+/-1 digit
<b>relative temperature-related measurement deviation</b>	5 %
<b>internal resistance of the measuring circuit</b>	500 mΩ

#### Precision

<b>relative metering precision</b>	5 %
<b>temperature drift per °C</b>	0.1 %/°C

#### Auxiliary circuit

<b>number of NC contacts delayed switching</b>	0
<b>number of NO contacts delayed switching</b>	0
<b>number of CO contacts delayed switching</b>	1
<b>operating frequency with 3RT2 contactor maximum</b>	5 000 1/h

#### Main circuit

<b>number of poles for main current circuit</b>	1
<b>operating voltage rated value</b>	24 ... 240 V
<b>ampacity of the output relay at AC-15</b>	
• at 250 V at 50/60 Hz	3 A
• at 400 V at 50/60 Hz	3 A
<b>ampacity of the output relay at DC-13</b>	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A
<b>operational current at 17 V minimum</b>	0.005 A
<b>continuous current of the DIAZED fuse link of the output relay</b>	4 A

#### Electromagnetic compatibility

<b>conducted interference</b>	
• due to burst according to IEC 61000-4-4	2 kV
• due to conductor-earth surge according to IEC 61000-4-5	2 kV
• due to conductor-conductor surge according to IEC 61000-4-5	1 kV
<b>field-based interference according to IEC 61000-4-3</b>	10 V/m
<b>electrostatic discharge according to IEC 61000-4-2</b>	6 kV contact discharge / 8 kV air discharge

#### Galvanic isolation

<b>design of the electrical isolation</b>	Protective separation
<b>galvanic isolation</b>	
• between input and output	Yes
• between the outputs	Yes
• between the voltage supply and other circuits	Yes

#### Connections/ Terminals

<b>product component removable terminal for main circuit</b>	Yes
<b>product component removable terminal for auxiliary and control circuit</b>	Yes
<b>type of electrical connection</b>	
• for main current circuit	spring-loaded terminals

- for auxiliary and control circuit

#### type of connectable conductor cross-sections

- solid
- finely stranded with core end processing
- finely stranded without core end processing
- at AWG cables solid
- at AWG cables stranded

#### connectable conductor cross-section

- solid
- finely stranded with core end processing
- finely stranded without core end processing

#### AWG number as coded connectable conductor cross section

- solid
- stranded

spring-loaded terminals

2x (0.25 ... 1.5 mm<sup>2</sup>)  
 2 x (0.25 ... 1.5 mm<sup>2</sup>)  
 2x (0.25 ... 1.5 mm<sup>2</sup>)  
 2x (24 ... 16)  
 2x (24 ... 16)

0.25 ... 1.5 mm<sup>2</sup>  
 0.25 ... 1.5 mm<sup>2</sup>  
 0.25 ... 1.5 mm<sup>2</sup>

24 ... 16  
 24 ... 16

### Installation/ mounting/ dimensions

#### mounting position

any

#### fastening method

snap-on mounting

#### height

94 mm

#### width

22.5 mm

#### depth

91 mm

#### required spacing

- with side-by-side mounting
  - forwards
  - backwards
  - upwards
  - downwards
  - at the side
- for grounded parts
  - forwards
  - backwards
  - upwards
  - at the side
  - downwards
- for live parts
  - forwards
  - backwards
  - upwards
  - downwards
  - at the side

0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm  
 0 mm

### Ambient conditions

installation altitude at height above sea level maximum

2 000 m

#### ambient temperature

- during operation
- during storage
- during transport

-25 ... +60 °C  
 -40 ... +85 °C  
 -40 ... +85 °C

### Certificates/ approvals

#### General Product Approval

EMC

Declaration of  
Conformity

[Confirmation](#)



Declaration of  
Conformity

Test Certificates

Marine / Shipping

other



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



[Confirmation](#)

[Vibration and Shock](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4621-2AW30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4621-2AW30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3UG4621-2AW30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UG4621-2AW30&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UG4621-2AW30&lang=en)

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3UG4621-2AW30/manual>



last modified:

12/21/2020