## **SIEMENS**

Data sheet US2:52BP2K9



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 600V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Amber Lens 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Figure similar

design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
color of the actuating element	amber	
material of the actuating element	metal mushroom head with plastic lens	
type of unlocking device	pull-to-unlatch mechanism	
number of switching positions	2	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	black	
Holder		
material of the holder	Metal	
Contact block/ lampholder		
socket design	BA 9s with lamp	
number of lampholders	1	
Display		
number of LED modules	0	
General technical data		
product component		
<ul> <li>lamp transformer</li> </ul>	Yes	
• light source	Yes	
degree of pollution	1	
type of voltage		
<ul> <li>of the operating voltage</li> </ul>	AC	
of the input voltage	AC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
<ul> <li>of the terminal</li> </ul>	IP20	
Supply voltage		
type of voltage of the supply voltage of the light source	AC	
supply voltage of the light source at AC at 60 Hz		
rated value	6 V	
Inputs/ Outputs		
output voltage 1 of the lamp transformer rated value	6 V	

Connections/ Terminals		
type of electrical connection	screw-type terminals	
of modules and accessories	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
Lamp		
type of light source	filament lamp	
color of the light source	clear	
Safety related data		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-35 +70 °C	
<ul> <li>during storage</li> </ul>	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2K9

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2K9

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2K

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52BP2K9&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52BP2K9&lang=en</a>

last modified:	5/31/2021