SIEMENS

Data sheet

US2:52BP2KR



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 600V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Aduator round number of command points 1 faciosare 1 delivery state as a kit No Actuator product extension optional light source Yes material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes product extension optional light source Yes fort ring pull-to-unlatch mechanism number of switching positions 2 Front ring standard material of the front ring metal color of the front ring metal Contact block/ lampholder Metal Contact block/ lampholders 1 outset of LED modules 0 General technical data Product component unmber of LED modules 0 General technical data Yes elight source Yes elight source Yes elight source Yes of the operaling voltage AC of the operaling voltage AC of the input voltage AC of the input voltage AC of the input voltage AC		
number of command points 1 delivery state as a kit No Actuator Product extension optional light source Yes material of the actuating element plastic plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Product component front ring Yes design of the front ring metal color of the front ring metal delick Holder material of the holder Metal Metal Metal Contract block/ lampholder socket design BA 9s with lamp mumber of lampholder socket design BA 9s with lamp number of LED modules 0 General technical data product component • I Plastic Plastic Plastic ves degrees of pollution 1 1 Plastic Plast		Actuator round
delivery state as a kit No Actuator		
Actuator Product extension optional light source Yes material of the actuating olement plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring product component front ring Yes design of the front ring metal color of the front ring material of the holder Metal Contract light source Contract block/ lampholders 1 Display number of LED modules 0 Ceneral technical data product component Yes es e light source Yes Yes degree of pollution 1 type of voltage of the operating voltage AC AC e of the operating voltage AC Surge voltage resistance rated value e of the input voltage AC Surgely voltage AC surge voltage of the light source at AC at 60 Hz e V Surphy voltage AC surge voltage of the light source at AC at 60 Hz e voltage of the light source AC of the terminal IP20 Surphy voltage of the light source AC surgely v		
product extension optional light source Yes material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring Metal color of the front ring Islack Holder Metal color of the front ring Islack Holder Metal color of the front ring Black Holder Metal context block/ lampholder Socket design socket design BA 9s with lamp number of LED modules 0 General technical data Product component • light source Yes • light source Yes • of the operating voltage AC • of the operating voltage AC • of the input voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 v of the terminal IP20 <td></td> <td>No</td>		No
material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring metal color of the front ring black Holder metal material of the holder Metal Contact block/ lampholder 1 socket design BA 9s with lamp number of LED modules 0 General technical data 1 product component • • light source Yes • light source Yes • light source Yes • of the operating voltage AC • of the operating voltage AC • of the operating voltage AC • of the terminal IP20 Supply voltage AC • of the light source at AC at 60 Hz 6 V • atted value f V • atted value </td <td>Actuator</td> <td></td>	Actuator	
type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring Standard material of the front ring metal color of the front ring metal color of the front ring Metal Contact block/ lampholder Metal contact block/ lampholder 0 socket design As 9 swith lamp number of LED modules 0 General technical data	product extension optional light source	Yes
number of switching positions 2 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder metal color of the front ring black Holder metal color of the front ring black Holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data product component • light source Yes elight source Yes degree of pollution 1 type of voltage AC • of the input voltage AC • of the input voltage AC • of the terminal IP20 Surge voltage resistance rated value 4 kV protection class IP IP66 • of the light source at AC at 60 Hz 6 V * pot voltage of the light source at AC at 60 Hz 6 V inputs	material of the actuating element	
Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal contact block/lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data 0 general technical data Yes product component Yes • light source Yes degree of pollution 1 type of voltage AC • of the input voltage AC • of the terminal IP20 Supply voltage AC • of the terminal IP20 Supply voltage of the light source AC • of the terminal IP20 Supply voltage of the light source AC • of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 6 V • puts/ Outputs GV • output voltage of the light source at AC at 60 Hz 6 V • output voltage of the light source at AC at 60 Hz 6 V	type of unlocking device	pull-to-unlatch mechanism
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder Socket design socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data 0 ingh transformer Yes e light source Yes of the input voltage AC e of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V inputs/ Outputs 6 V	number of switching positions	2
design of the front ring standard material of the front ring black color of the front ring black tolder material of the holder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data 0 product component Ves • light source Yes • light source Yes • of the operating voltage AC • of the operating voltage AC • of the terminal IP20 Supply voltage AC • of the terminal IP20 Supply voltage of the light source AC surge voltage of the light source at AC at 60 Hz 6 V • rated value 6 V	Front ring	
material of the front ring metal color of the front ring black Holder material of the holder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data 0 general technical data 0 of the operating voltage Yes • light source Yes • of the operating voltage AC • of the operating voltage AC • of the input voltage AC • of the emminal IP20 Supply voltage IP20 Supply voltage AC • of the terminal IP20 Supply voltage of the light source AC • of voltage of the light source at AC at 60 Hz • rated value • rated value 6 V	product component front ring	Yes
color of the front ring black material of the holder Metal Contact block/ lampholder Socket design socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data 0 general technical data 0 general technical data 0 of the operating voltage Yes of the operating voltage AC of the operating voltage AC surge voltage resistance rated value 4 kV protect on class IP IP66 of the terminal IP20 Supply voltage AC surge voltage of the light source AC surge voltage of the light source AC surge voltage of the light source AC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the light source at AC at 60 Hz For voltage of the light source at C at 60 Hz of the datage of the light source at AC at 60 Hz For voltage 1 of the lamp	design of the front ring	standard
Holder Metal Contact block/ lampholder BA 9s with lamp socket design BA 9s with lamp number of lampholders 1 Display 0 General tachnical data 0 product component 4 • lamp transformer Yes • light source Yees degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV prototage IP20 Supply voltage AC surge voltage of the light source AC surge voltage rated value 4 kV protection class IP IP20 Supply voltage of the light source AC at 60 Hz Filtered • rated value 6 V Inputs/ Outputs 6 V	material of the front ring	metal
material of the holder Metal Contact block/ lampholder BA 9s with lamp socket design BA 9s with lamp number of lampholders 1 Display 0 number of LED modules 0 General technical data 0 product component 1 • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V	color of the front ring	black
Contact block/ lampholder socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 1 type of voltage 4 of the operating voltage AC of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 6 V erated value 6 V Inputs/ Outpu	Holder	
socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 groduct component 0 • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	material of the holder	Metal
number of lampholders 1 Display 0 number of LED modules 0 General technical data 0 groduct component Ves • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source AC AC supply voltage of the light source to the light source AC Supply voltage of the light source to the light	Contact block/ lampholder	
Display 0 General technical data 0 groduct component 1 • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC surge voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	socket design	BA 9s with lamp
number of LED modules 0 General technical data	number of lampholders	1
General technical data product component • lamp transformer • light source Yes degree of pollution 1 type of voltage • of the operating voltage • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP • of the terminal IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz • rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	Display	
product component Yes e lamp transformer Yes e light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	number of LED modules	0
• lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC surge to voltage of the light source AC supply voltage of the light source at AC at 60 Hz - • rated value 6 V Inputs/ Outputs 6 V	General technical data	
• light source Yes degree of pollution 1 type of voltage 1 • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V	product component	
degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V inputs/ Outputs 6 V	 lamp transformer 	Yes
type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz AC • rated value 6 V Inputs/ Outputs 6 V	light source	Yes
• of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz AC • rated value 6 V Inputs/ Outputs 6 V	degree of pollution	1
• of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz AC • rated value 6 V Inputs/ Outputs 6 V	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage IP20 type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	 of the operating voltage 	AC
protection class IP IP66 • of the terminal IP20 Supply voltage IP20 type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	 of the input voltage 	AC
• of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	surge voltage resistance rated value	4 kV
Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	protection class IP	IP66
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	of the terminal	IP20
supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	Supply voltage	
rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	type of voltage of the supply voltage of the light source	AC
Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	supply voltage of the light source at AC at 60 Hz	
output voltage 1 of the lamp transformer rated value 6 V	rated value	6 V
	Inputs/ Outputs	
Connections/ Terminals	output voltage 1 of the lamp transformer rated value	6 V
	Connections/ Terminals	

type of electrical connection	screw-type terminals	
 of modules and accessories 	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf-in] with screw-type terminals	8 8 lbf·in	
Lamp		
type of light source	filament lamp	
color of the light source	clear	
Safety related data		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
 during storage 	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Siemens has decided to exit the Russian market (see here).		
https://press.siemens.com/global/en/pressrelease/siemens-wind-d		
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an		
EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).		
Information on the packaging		
https://support.industry.siemens.com/cs/ww/en/view/109813875		
Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10		
Industry Mall (Online ordering system)		
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2KR		
Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2KR		
Service&Support (Manuals, Certificates, Characteristics, FAQ	s,)	
https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2KR		
Image database (product images, 2D dimension drawings, 3D http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US		
nup.//www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US	2.32DF2NRaidiy-til	

last modified:

5/31/2021 🖸