SIEMENS

Data sheet

US2:52BP3JB



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 480V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with White Lens 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
color of the actuating element	white
material of the actuating element	metal mushroom head with plastic lens
type of unlocking device	without
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with lamp
number of lampholders	1
Display	
number of LED modules	0
General technical data	
product component	
lamp transformer	Yes
light source	Yes
degree of pollution	1
type of voltage	
 of the operating voltage 	AC
 of the input voltage 	AC
surge voltage resistance rated value	4 kV
protection class IP	IP66
• of the terminal	IP20
Supply voltage	
type of voltage of the supply voltage of the light source	AC
supply voltage of the light source at AC at 60 Hz	
rated value	6 V
Inputs/ Outputs	
output voltage 1 of the lamp transformer rated value	6 V
Connections/ Terminals	

be of electrical connection	screw-type terminals
 of modules and accessories 	Screw-type terminal
htening torque of the screws in the bracket	20 N·m
ntening torque [lbf·in] with screw-type terminals	8 8 lbf-in
p	
be of light source	filament lamp
lor of the light source	clear
ty related data	
uch protection against electrical shock	finger-safe
ient conditions	
ibient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
allation/ mounting/ dimensions	
ape of the installation opening	round
ificates/ approvals	
her information	
emens has decided to exit the Russian market (see here)	
ps://press.siemens.com/global/en/pressrelease/siemens-win	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an	
EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).	
Information on the packaging	
https://support.industry.siemens.com/cs/ww/en/view/109813875	
ormation- and Downloadcenter (Catalogs, Brochures,)	
ps://www.siemens.com/ic10	
lustry Mall (Online ordering system)	
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?r x online generator	
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?r	nlfb=US2:52BP3JB
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?r x online generator p://support.automation.siemens.com/WW/CAXorder/default.a rvice&Support (Manuals, Certificates, Characteristics, FA	nlfb=US2:52BP3JB aspx?lang=en&mlfb=US2:52BP3JB AQs,)
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?r x online generator p://support.automation.siemens.com/WW/CAXorder/default.a rvice&Support (Manuals, Certificates, Characteristics, F ps://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3.	nlfb=US2:52BP3JB aspx?lang=en&mlfb=US2:52BP3JB AQs,) IB
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?r x online generator p://support.automation.siemens.com/WW/CAXorder/default.a rvice&Support (Manuals, Certificates, Characteristics, FA	nlfb=US2:52BP3JB aspx?lang=en&mlfb=US2:52BP3JB AQs,) IB 3D models, device circuit diagrams, EPLAN macros,)

last modified:

5/31/2021 🖸