## **SIEMENS**

Data sheet US2:52PP7DTXB

30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 24V AC/DC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
color of the actuating element	amber	
material of the actuating element	plastic	
type of unlocking device	pull-to-unlatch mechanism	
number of switching positions	3	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	chrome	
Holder		
material of the holder	Metal	
Contact block/ lampholder		
socket design	BA 9s with LED	
number of lampholders	1	
Display		
number of LED modules	1	
General technical data		
product component		
lamp transformer	No	
• light source	Yes	
degree of pollution	1	
type of voltage		
<ul> <li>of the operating voltage</li> </ul>	AC/DC	
<ul> <li>of the input voltage</li> </ul>	AC/DC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
of the terminal	IP20	
operating voltage		
<ul> <li>at AC at 60 Hz rated value</li> </ul>	24 28 V	
<ul> <li>at DC rated value</li> </ul>	24 28 V	
Supply voltage		
type of voltage of the supply voltage of the light source	AC/DC	
supply voltage of the light source at AC at 60 Hz		
rated value	28 24 V	
supply voltage of the light source at DC		
• rated value	28 24 V	
Connections/ Terminals		
type of electrical connection	screw-type terminals	
of modules and accessories	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
ughtering torque [ibi iii] with screw-type terminals		

type of light source	LED	
color of the light source	yellow	
Safety related data		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP7DTXB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP7DTXB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP7DTXB&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP7DTXB&lang=en</a>

	_
last modified:	5/31/2021 🗗