

Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Selector switch operators

Selection and ordering data

Version	Lever type	Color of lever insert	Cam Code ²⁾	Input Voltage	Order no.	Pack unit	
Selector Switches with 2 switching positions							
Maintained operation	Non-Illuminated, short lever	White	A		52SA2AAB	1	
	Non-Illuminated, long lever	White	A		52SB2AAB	1	
	Illuminated, short lever ¹⁾ with full voltage 24V, 755 type lamp		A	24V	52SA7ADN	1	
	Illuminated, short lever ¹⁾ with 50/60 Hz transformer 6V, 755 type lamp		A	120V 240V	52SA7AGN 52SA7AHN	1	
Spring return from right operation	Non-Illuminated, short lever	White	A		52SA2ACB	1	
	Non-Illuminated, long lever	White	A		52SB2ACB	1	
Selector Switches with 3 switching positions							
Maintained operation	Non-Illuminated, short lever	White	B		52SA2BAB	1	
	Non-Illuminated, long lever	White	B		52SB2BAB	1	
	Non-Illuminated, short lever	White	C ³⁾		52SA2CAB	1	
	Non-Illuminated, long lever	White	C ³⁾		52SB2CAB	1	
	Non-Illuminated, short lever	White	D		52SA2DAB	1	
	Non-Illuminated, long lever	White	D		52SB2DAB	1	
	Non-Illuminated, short lever	White	E		52SA2EAB	1	
	Non-Illuminated, long lever	White	E		52SB2EAB	1	
	Non-Illuminated, short lever	White	G		52SA2GAB	1	
	Non-Illuminated, long lever	White	G		52SB2GAB	1	
	Illuminated, short lever ¹⁾ with full voltage 24V, 755 type lamp		B C ³⁾	24V 24V	52SA7BDN 52SA7CDN	1	
	Illuminated, short lever ¹⁾ with 50/60 Hz transformer 6V, 755 type lamp		B C ³⁾	120V 120V 240V 240V	52SA7BGN 52SA7CGN 52SA7BHN 52SA7CHN	1	
	Spring return from right operation	Non-Illuminated, short lever	White	B		52SA2BCB	1
		Non-Illuminated, long lever	White	B		52SB2BCB	1
Non-Illuminated, short lever		White	C ³⁾		52SA2CCB	1	
Non-Illuminated, long lever		White	C ³⁾		52SB2CCB	1	
Non-Illuminated, short lever		White	D		52SA2DCB	1	
Non-Illuminated, long lever		White	D		52SB2DCB	1	
Non-Illuminated, short lever		White	E		52SA2ECB	1	
Non-Illuminated, long lever		White	E		52SB2ECB	1	
Non-Illuminated, short lever		White	G		52SA2GCB	1	
Non-Illuminated, long lever		White	G		52SB2GCB	1	
Spring return from left operation		Non-Illuminated, short lever	White	B		52SA2BBB	1
		Non-Illuminated, long lever	White	B		52SB2BBB	1
	Non-Illuminated, short lever	White	C ³⁾		52SA2CBB	1	
	Non-Illuminated, long lever	White	C ³⁾		52SB2CBB	1	
	Non-Illuminated, short lever	White	D		52SA2DBB	1	
	Non-Illuminated, long lever	White	D		52SB2DBB	1	
	Non-Illuminated, short lever	White	E		52SA2EBB	1	
	Non-Illuminated, long lever	White	E		52SB2EBB	1	
	Non-Illuminated, short lever	White	G		52SA2GBB	1	
	Non-Illuminated, long lever	White	G		52SB2GBB	1	
	Spring return from left and right operation	Non-Illuminated, short lever	White	B		52SA2BDB	1
		Non-Illuminated, long lever	White	B		52SB2BDB	1
Non-Illuminated, short lever		White	C ³⁾		52SA2CDB	1	
Non-Illuminated, long lever		White	C ³⁾		52SB2CDB	1	
Non-Illuminated, short lever		White	D		52SA2DDB	1	
Non-Illuminated, long lever		White	D		52SB2DDB	1	
Non-Illuminated, short lever		White	E		52SA2EDB	1	
Non-Illuminated, long lever		White	E		52SB2EDB	1	
Non-Illuminated, short lever		White	G		52SA2GDB	1	
Non-Illuminated, long lever		White	G		52SB2GDB	1	
Selector Switches with 4 switching positions							
Maintained operation		Non-Illuminated, short lever	White	H		52SA2HAB	1
	Non-Illuminated, long lever	White	H		52SB2HAB	1	

1) Illuminated selector switches are provided without lenses. Lens kit must be ordered separately on page 10/154.

2) For contact operation, see cam selection chart on page 10/151.


3) The C cam is limited to 4 contact blocks, 1 or 2 pole.

Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Selector switch operators

Selection and ordering data

Version	Color of lever insert	Cam Code ²⁾	Order no.	nit
 <p>Selector Pushbutton Operators</p> <p>NEMA 12/13 only Flush type cap</p> <p>1/2" raised type cap</p>	Black	P	52SA3P1	1
	Black	Q	52SA3Q1	
	Black	R	52SA3R1	
	Red	P	52SA3P2	1
	Red	Q	52SA3Q2	
	Red	R	52SA3R2	
	Black	S	52SA3S1	1
	Red	S	52SA3S2	
	Black	P	52SA4P1	1
	Black	Q	52SA4Q1	
	Black	R	52SA4R1	
	Red	P	52SA4P2	1
Red	Q	52SA4Q2		
Red	R	52SA4R2		
Black	S	52SA4S1	1	
Red	S	52SA4S2		

1) For contact operation, see cam selection chart on page 10/151.