

# FLKM 4-I/O-G4 - Optocoupler module



5521322

<https://www.phoenixcontact.com/us/products/5521322>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE 4-channel module for solid state relays



## Your advantages

- Modules accept Opto 22 G4 or Grayhill G5 solid state relays
- Solid-state relay includes fuse and status indicator
- Can be fitted with solid-state relays or I/O modules

## Commercial data

Item number	5521322
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C460
Product key	CK6165
GTIN	4046356683814
Weight per piece (including packing)	110.2 g
Weight per piece (excluding packing)	110.2 g
Customs tariff number	85364190
Country of origin	US

# FLKM 4-I/O-G4 - Optocoupler module



5521322

<https://www.phoenixcontact.com/us/products/5521322>

## Technical data

### Product properties

Product type	Multi-channel solid-state relay module
No. of channels	4
Compatible components	Digital I/O modules
With components	no

### Input data

Input voltage range	4 V DC ... 32 V DC
Typical input current at $U_N$	30 mA (Optocoupler dependent)

### Output data

Compatible components	Digital I/O modules
-----------------------	---------------------

### Switching

Limiting continuous current	4 A
Error detection (line break / short-circuit)	no

### Connection data

#### Input

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Number of connections	1
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 14

### Dimensions

Width	67.5 mm
Height	77 mm
Depth	42 mm

### Material specifications

Color	green (RAL 6021)
Housing insulation material	PVC, side panel PA non-reinforced,

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

### Mounting

# FLKM 4-I/O-G4 - Optocoupler module



5521322

<https://www.phoenixcontact.com/us/products/5521322>

Assembly instructions	in rows with zero spacing
Mounting position	any

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)