



NEOZED, fuse base, D01, 3-pole, 16 A, Un AC: 400 V, Un DC: 250 V with twofold frame terminal

Model	
product brand name	NEOZED
product designation	Fuse base
design of the product	NEOZED fuse base installation
General technical data	
number of poles	3
size of fuse system according to EN 60269-1	D01
Supply voltage	
operating voltage rated value	400 V
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	0.6 W
operational current	
• at 35 °C rated value	15.36 A
• at 40 °C rated value	15.04 A
• at 45 °C rated value	14.72 A
• at 50 °C rated value	14.4 A
• at 55 °C rated value	14.08 A
• at 60 °C rated value	13.76 A
• at 65 °C rated value	13.28 A
• at 70 °C rated value	12.96 A
Main circuit	
operational current rated value	16 A
Product details	
product component cover	Yes
Mechanical Design	
height	83 mm
width	81 mm
depth	64 mm
fastening method	DIN rail
net weight	388 g
material of D fuse base	plastic
General Product Approval	
Declaration of Conformity	
Test Certificates	

[Confirmation](#)



[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

[Environmental Con-  
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG5301>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG5301>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SG5301](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG5301)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





