



Similar to image

Technical data:

Material		others
Appearance		shiny
Design of the operating mechanism		pushbutton/momentary pushbutton
Number of actuating rockers		1
Design of the product		single pushbutton
Design of the switching function		1 changeover contact
Type of mounting		surface mounted
Color		grey
Surface processing		others
Type of composition		basic element with complete enclosure
Breaking capacity current	A	10
Operating voltage / nominal value	V	230
material / of the housing		plastic
Product feature / halogen-free		Yes
Product component / Signaling contact		No
Product component / Lettering field		No
Product component / integrated / Fluorescent materials		No
Protection class IP		IP44

type of the assembly

fixing with screw

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Global Industry Mall (Online ordering system)


<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/5TD4707/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TD4707



last change:

Dec 6, 2010