6GK5008-0GA10-1AB2

Data sheet



SCALANCE XB008G unmanaged Industrial Ethernet Switch for 10/100/1000 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V DC power supply, with 8x 10/100/1000 Mbit/s RJ45 ports electrical Manual available as a download .

product type designation	SCALANCE XB008G
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
interfaces / for communication / maximum configuration for modular devices	
number of electrical ports / maximum	8
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	8; RJ45
number of 100 Mbit/s SC ports	
• for multimode	0
interfaces / other	
number of electrical connections	
for power supply	1
type of electrical connection	
for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	12.5 W
 supply voltage / 1 / rated value 	19.2 28.8 V
consumed current / 1 / maximum	0.52 A
 type of electrical connection / 1 / for power supply 	3-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
 fuse protection type / 1 / at input for supply voltage 	0.6 A / 60 V
ambient conditions	
ambient temperature	
 during operation 	-10 +60 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
design	Вох
width	45 mm
height	100 mm
depth	87 mm
net weight	0.188 kg
fastening method	

	information, visit http://support.automation.siemens.com. (V3.4)
Security information	support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more
security information	Siemens provides products and solutions with industrial security functions that
to website: industry Online Support security information	inthe weah had a second
 to website: CAx-Download-Manager to website: Industry Online Support 	https://support.industry.siemens.com
to website: Image database to website: CAx Download Manager	http://automation.siemens.com/bilddb http://www.siemens.com/cax
to website: Information and Download Center to website: Image database	http://www.siemens.com/industry/infocenter
to website: Industry Mall to website: Information and Download Contor	https://mall.industry.siemens.com
to web page: selection aid TIA Selection Tool to website: Industrial communication	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net
internet link	http://www.ciemens.com/tig.celection.tool
further information / internet links	
KC approval	Yes
• C-Tick	Yes
certificate of suitability	EN 61000-6-2, EN 61000-6-4
standards, specifications, approvals / other	
marking	
CCC / for hazardous zone according to GB standard / as	Ex nA IIC T4 Gc
CCC / for hazardous zone according to GB standard	Yes
certificate of suitability	VIVI ENVITOR
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
standards, specifications, approvals / hazardous environments	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / CE	
• according to IEC 81346-2:2019	KFE
• according to IEC 81346-2	KF
reference code	
MTBF	112 a
for interference immunity	EN 61000-6-2
• for emitted interference	EN 61000-6-4 (Class B)
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
standard	
standards, specifications, approvals	
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No
Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
product function	·
product functions / redundancy	
product function / switch-managed	No
PROFINET conformity class	A
• CoS	Yes
multiport mirroring	No
product function	
product functions / management, configuration, engineering	
S7-1500 rail mounting	No
wall mounting	Yes
 35 mm top hat DIN rail mounting 	Yes