



SCALANCE XB213-3LD managed layer 2 IE switch 13x 10/100 Mbit/s RJ45 ports, 3x SM FO SC-port 1x console port, diagnostics LED, redundant power supply, IEC 62443-4-2 certified; temperature range 0 °C to +60 °C; DIN-rail mounting; default EtherNet/IP.

product type designation	SCALANCE XB213-3LD
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
number of ports / maximum	16
interfaces / for communication / maximum configuration for modular devices	
number of electrical ports / maximum	13
number of optical ports / maximum	3
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	13; RJ45
number of 100 Mbit/s SC ports	
• for single mode (LD)	3
interfaces / other	
number of electrical connections	
• for operator console	1
• for management purposes	1
• for power supply	1
type of electrical connection	
• for operator console	RJ11
• for management purposes	RJ45
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
• supply voltage / 1 / rated value	24 V
• power loss [W] / 1 / rated value	9.6 W
• supply voltage / 1 / rated value	19.2 ... 28.8 V
• consumed current / 1 / maximum	0.4 A
• type of electrical connection / 1 / for power supply	6-pole terminal block
• product component / 1 / fusing at power supply input	Yes
ambient conditions	
ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Box

<ul style="list-style-type: none"> redundancy protocol / is supported / Media Redundancy Protocol (MRP) Yes product function <ul style="list-style-type: none"> • media redundancy protocol (MRP) with redundancy manager Yes • Media Redundancy Protocol Interconnection (MRP-I) Yes • redundancy procedure STP Yes • redundancy procedure RSTP Yes • redundancy procedure RSTP+ Yes • Parallel Redundancy Protocol (PRP)/operation in the PRP-network No • passive listening Yes protocol / is supported <ul style="list-style-type: none"> • LACP Yes 	
product functions / security	
<ul style="list-style-type: none"> product function <ul style="list-style-type: none"> • ACL - MAC-based Yes • ACL - port/MAC-based Yes • IEEE 802.1x (radius) Yes • broadcast/multicast/unicast limiter Yes • broadcast blocking Yes protocol / is supported <ul style="list-style-type: none"> • SSH Yes • SSL Yes 	
product functions / time	
<ul style="list-style-type: none"> product function <ul style="list-style-type: none"> • SICLOCK support Yes • NTP-client Yes • SNTP client Yes protocol / is supported <ul style="list-style-type: none"> • SNTP Yes 	
standards, specifications, approvals	
<ul style="list-style-type: none"> standard <ul style="list-style-type: none"> • for emitted interference EN 61000-6-4 (Class A) • for interference immunity EN 61000-6-2 IT security for industrial automation systems / according to IEC 62443-4-2:2019 Yes reference code <ul style="list-style-type: none"> • according to IEC 81346-2 KF • according to IEC 81346-2:2019 KFE 	
standards, specifications, approvals / CE	
<ul style="list-style-type: none"> certificate of suitability / CE marking Yes certificate of suitability / RoHS conformity Yes; 2011/65/EU 	
standards, specifications, approvals / hazardous environments	
<ul style="list-style-type: none"> standard / for hazardous zone EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X certificate of suitability <ul style="list-style-type: none"> • CCC / for hazardous zone according to GB standard Yes 	
standards, specifications, approvals / other	
<ul style="list-style-type: none"> certificate of suitability EN 61000-6-2, EN 61000-6-4 <ul style="list-style-type: none"> • C-Tick Yes • KC approval Yes 	
further information / internet-Links	
<ul style="list-style-type: none"> Internet-Link <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool http://www.siemens.com/tia-selection-tool • to website: Industrial communication http://www.siemens.com/simatic-net • to website: Industry Mall https://mall.industry.siemens.com • to website: Information and Download Center http://www.siemens.com/industry/infocenter • to website: Image database http://automation.siemens.com/bilddb • to website: CAx-Download-Manager http://www.siemens.com/cax • to website: Industry Online Support https://support.industry.siemens.com 	

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

9/16/2022 