



Connection sets



BEM... connections

E0744D




BEM75-30

E0618D1



BEM300-30

1SFT98001-011C3




BES... for 3-pole connections

E0860D




BES...

1SFT98000-009C6



BES... for 4 N.O. main pole connections

E0743D



BES75-40

E0461D1

Connection sets for reversing contactors

Description

Connections between the main poles of two 3-pole contactors mounted side by side as reversing contactors. The sets are made up of three upstream connections and three downstream connections.

- BER40V – Insulated, stranded, rigid copper wires
- BEM75-30 ... BEM750-30 – Insulated, solid copper bars

On the A... contactors, the power supply by bars or cables equipped with lugs is directly connected to the terminal pads of the main poles. For flange connectors, LX... terminal extension pieces should be used.

Ordering details

For 3-pole contactors	Type	Order code	Pkg qty	Weight (1 pce) kg
A40	BER40V	1SBN082411R1000	1	0.085
A50 ... A75	BEM75-30	1SBN083501R1000	1	0.243
A95, A110	BEM110-30	1SFN084301R1000	1	0.450
A145, A185	BEM185-30	1SFN084701R1000	1	0.900
A210 ... A300	BEM300-30	1SFN085101R1000	1	1.100
AF400, AF460	BEM460-30	1SFN085701R1000	1	4.400
AF580, AF750	BEM750-30	1SFN086101R1000	1	7.300

Note: The connections provided for the A... contactors can be used for the AF, AL, TAL, AE and TAE types.

3-pole connections phase to phase

Description

Connections between the main poles of two 3-pole contactors horizontal mounted. This set is made up of three downstream or upstream connections.

Ordering details

For 3-pole contactors	Type	Order code	Pkg qty	Weight (1 pce) kg
A50 ... A75	BES75-30	1SBN083504R1000	1	0.130
A95, A110	BES110	1SFN084304R1000	1	0.250
A145, A185	BES185	1SFN084704R1000	1	0.500
A210 ... A300	BES300	1SFN085104R1000	1	1.000
AF400, AF460	BES460	1SFN085704R1000	1	2.200
AF580, AF750	BES750	1SFN086104R1000	1	3.700

Note: The connections provided for the A... contactors can be used for the AF, AE and TAE types.

Connections for 4-pole changeover contactors

Description

Connection between the main poles of two 4-pole contactors mounted side by side so that they operate as source reversing contactors.

These sets are made up of four downstream connections, with insulated, stranded, rigid copper cables.

Ordering details

For 4-pole contactors	Type	Order code	Pkg qty	Weight (1 pce) kg
A45, A50, A75	BES75-40	1SBN083302R1000	1	0.400

Note: The connections provided for the A... contactors can be used for the AF, AE and TAE types.