

# Product data sheet

Specifications



servo motor BMH, Lexium 32,  
30Nm, 5000rpm, keyed shaft, with  
brake, IP65, IP67, 128 multiturn  
encoder

BMH1901P32F2A

**Product availability: Non-Stock - Not normally stocked in distribution facility**

**Price\*: 4,006.00 USD**

## Main

<b>Device short name</b>	BMH
<b>Product or Component Type</b>	Servo motor
<b>Maximum mechanical speed</b>	4000 rpm
<b>Continuous stall torque</b>	265.5 lbf.in (30 N.m) LXM32.D72N4 24 A, 400 V, three phase 265.5 lbf.in (30 N.m) LXM32.D72N4 24 A, 480 V, three phase 265.5 lbf.in (30 N.m) LXM32MD85N4 32 A, 400 V, three phase 265.5 lbf.in (30 N.m) LXM32MD85N4 32 A, 480 V, three phase 265.5 lbf.in (30 N.m) LXM32MC10N4 40 A, 400 V, three phase 265.5 lbf.in (30 N.m) LXM32MC10N4 40 A, 480 V, three phase
<b>Peak stall torque</b>	687.7 lbf.in (77.7 N.m) LXM32.D72N4 24 A, 400 V, three phase 687.7 lbf.in (77.7 N.m) LXM32.D72N4 24 A, 480 V, three phase 766.5 lbf.in (86.6 N.m) LXM32MD85N4 32 A, 400 V, three phase 766.5 lbf.in (86.6 N.m) LXM32MD85N4 32 A, 480 V, three phase 793.9 lbf.in (89.7 N.m) LXM32MC10N4 40 A, 400 V, three phase 793.9 lbf.in (89.7 N.m) LXM32MC10N4 40 A, 480 V, three phase
<b>Nominal output power</b>	4800 W LXM32.D72N4 24 A, 400 V, three phase 4800 W LXM32.D72N4 24 A, 480 V, three phase 5180 W LXM32MD85N4 32 A, 400 V, three phase 5180 W LXM32MD85N4 32 A, 480 V, three phase 5180 W LXM32MC10N4 40 A, 400 V, three phase 5180 W LXM32MC10N4 40 A, 480 V, three phase
<b>Nominal torque</b>	162.9 lbf.in (18.4 N.m) LXM32.D72N4 24 A, 400 V, three phase 162.9 lbf.in (18.4 N.m) LXM32.D72N4 24 A, 480 V, three phase 146.04 lbf.in (16.5 N.m) LXM32MD85N4 32 A, 400 V, three phase 146.04 lbf.in (16.5 N.m) LXM32MD85N4 32 A, 480 V, three phase 146.04 lbf.in (16.5 N.m) LXM32MC10N4 40 A, 400 V, three phase 146.04 lbf.in (16.5 N.m) LXM32MC10N4 40 A, 480 V, three phase
<b>Nominal speed</b>	2500 rpm LXM32.D72N4 24 A, 400 V, three phase 2500 rpm LXM32.D72N4 24 A, 480 V, three phase 3000 rpm LXM32MD85N4 32 A, 400 V, three phase 3000 rpm LXM32MD85N4 32 A, 480 V, three phase 3000 rpm LXM32MC10N4 40 A, 400 V, three phase 3000 rpm LXM32MC10N4 40 A, 480 V, three phase
<b>Product compatibility</b>	LXM32.D72N4 400...480 V three phase
<b>Shaft end</b>	Keyed
<b>IP Degree of Protection</b>	IP65 standard IP67 with IP67 kit
<b>Speed feedback resolution</b>	131072 points/turn x 4096 turns
<b>Holding brake</b>	With
<b>Mounting Support</b>	International standard flange
<b>Electrical Connection</b>	Rotatable right-angled connectors

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Complementary

Range Compatibility	Lexium 32
[Us] rated supply voltage	480 V
Phase	Three phase
Continuous stall current	23.2 A
Continuous power	5.24 W
Maximum current Irms	72 A LXM32.D72N4
Maximum permanent current	89.6 A
Second shaft	Without second shaft end
Shaft diameter	1.5 in (38 mm)
Shaft length	3.1 in (80 mm)
Key width	2.8 in (70 mm)
Feedback type	Multiturn SinCos Hiperface
Holding torque	708.06 lbf.in (80 N.m) holding brake
Motor flange size	7.5 in (190 mm)
Number of motor stacks	1
Torque constant	1.3 N.m/A 248.0000000000 °F (120 °C)
Back emf constant	87.6 V/krpm 248.0000000000 °F (120 °C)
Number of motor poles	10
Rotor inertia	71.7 kg.cm <sup>2</sup>
Stator resistance	0.24 Ohm 68.0000000000 °F (20 °C)
Stator inductance	5.08 mH 68.0000000000 °F (20 °C)
Stator electrical time constant	21.2 ms 68.0000000000 °F (20 °C)
Maximum radial force Fr	3730 N 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	40 W
Type of cooling	Natural convection
Length	9.8 in (250 mm)
Centring collar diameter	7.09 in (180 mm)
Centring collar depth	0.2 in (4 mm)
Number of mounting holes	4
Mounting holes diameter	0.6 in (14 mm)
Circle diameter of the mounting holes	8.5 in (215 mm)
Net Weight	45.2 lb(US) (20.5 kg)

## Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53
GTIN	3606485266152
Returnability	No
Country of origin	DE

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	15.7 in (40.0 cm)
<b>Package 1 Width</b>	11.4 in (29.0 cm)
<b>Package 1 Length</b>	31.5 in (80.0 cm)
<b>Package 1 Weight</b>	62.8 lb(US) (28.5 kg)
<b>Unit Type of Package 2</b>	P06
<b>Number of Units in Package 2</b>	2
<b>Package 2 Height</b>	30.3 in (77.0 cm)
<b>Package 2 Width</b>	31.5 in (80.0 cm)
<b>Package 2 Length</b>	23.6 in (60.0 cm)
<b>Package 2 Weight</b>	144.4 lb(US) (65.5 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Pvc Free

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>