

Product datasheet

Specifications



Flashing LED, 24 Vac/Vdc Red

DL1BKB4

Main

Range Compatibility	Harmony XVP Harmony XVB Harmony XVD
Accessory / Separate Part Designation	Protected LED bulb
Accessory / Separate Part Type	LED bulb
Accessory / Separate Part Categor	Lighting accessories
Accessory / Separate Part Destination	Beacon and indicator bank
[Us] Rated Supply Voltage	24 V AC/DC
Signalling Type	Flashing
Signalling Colour	Red
Sale Per Indivisible Quantity	1

Complementary

Current Consumption	47 mA
Bulb Base	BA 15d
Net Weight	0.015 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	4.5 cm
Package 1 Length	5.8 cm
Package 1 Weight	11.0 g
Unit Type Of Package 2	S01
Number Of Units In Package 2	60
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	924.0 g

Contractual warranty

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile No need of specific recycling operations