



Siemens Low Voltage Circuit Protection General Duty Safety Switches.
 Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 240V A. Rating:
 30 A No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material:
 304SS Enclosure: TYPE 3R. 2-3 point mounting holes. O. Cycles: 10000
 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental
 Conditions: OUTDOOR

mechanical service life (operating cycles) typical	10000
fastening method	SURFACE
number of poles	3
suitability for operation	DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS
Electricity	
ampacity	30 A
Environmental conditions	
ambient temperature during operation maximum	85 °C
ambient temperature during operation minimum	-29 °C
Model	
product brand name	SIEMENS
product sub brand name	VBII
product type designation	GENERAL DUTY SWITCH
special product feature	FACTORY INSTALLED COPPER LUGS
type of electrical connection	MECHANICAL LUGS
Mechanical Design	
design of the housing	TYPE 3R
design of the actuating element	SINGLE THROW
material	STEEL
General product approval	
certificate of suitability	UL98

last modified: 9/15/2021 

