



Representative Image

### Catalog No. GPS1BHAN

Description: MMS HIGH BK 14 - 20 AMPS

UPC No 4538915012468

Home > Starters > IEC > Manual Motor Starter - SURION

- MANUAL MOTOR STARTER T+M PROT. GPS1 14-20A HIGH BREAKING  
- Pack-5

#### Descriptors

Category	Manual Motor Starter - SURION
GO Schedule	CC

#### Specifications

Rated Current	20.0 A
Capacity	GPS1BH - High breaking capacity
Instantaneous short-circuit release (A)	260
Rated power 3 phase motors at 220/230Vac Pn (hp)	4
Rated power 3 phase motors at 400Vac Pn (hp)	5
Rated power 3 phase motors at 440Vac Pn (hp)	10
Rated power 3 phase motors at 500/525Vac Pn (hp)	15
Rated power 3 phase motors at 660/690Vac Pn (hp)	13 hp
Rated service short-circuit breaking cap 220/230V Ics kA	65
Rated service short-circuit breaking cap 400V Ics kA	50
Rated service short-circuit breaking cap 440V Ics kA	10
Rated service short-circuit breaking cap 500/525V Ics kA	8
Rated service short-circuit breaking cap 600V Ics kA	3
Rated service short-circuit breaking cap 690V Ics kA	3
Rated ultimate short-circuit breaking cap 220/230V Icu kA	65
Rated ultimate short-circuit breaking cap 400V Icu kA	25
Rated ultimate short-circuit breaking cap 440V Icu kA	25
Rated ultimate short-circuit breaking cap 500/525V Icu kA	10
Rated ultimate short-circuit breaking cap 600V Icu kA	4
Rated ultimate short-circuit breaking cap 690V Icu kA	4
Series	Surion - GPS1B - Thermal and magnetic protection (Ie max 32A)
Thermal current setting range (A)	14 - 20 A
Trip class IEC 60947-4-1	Class 10
Single Phase Horsepower @ 115V	1 1/2
Single Phase Horsepower @ 230V	3
FLA Adjustment Range	14 - 20 A
Max. Fuse Size (A)	80
Max Circuit Breaker Size (A)	80
Max. Fuse or Circuit Breaker Size - Group Installation (A)	500
Rated Breaking Capacity @ 277Y/480V - Combination Starter (kA)	50

**Specifications**

Minimum Contactor Size	CL02
GSA Compliance	No

**Dimensions**

Weight	0.79 lb
Width	45.0 mm