## SIEMENS

## Data sheet

## US2:HNF363X



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A. Rating: 100A Wattage: 3W No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material: NM Enclosure: TYPE 4X. 2-3 point mounting holes. Insulation: YES O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDUSTRIAL CORROSIVE RESISTANCE

	IIIIIIa	

mechanical service life (operating cycles) typical fastening method number of poles suitability for operation	10000 SURFACE 3 DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS			
Electricity				
ampacity	100 A			
supply voltage frequency rated value 50/60 Hz	Yes			
Model				
product brand name	SIEMENS			
product type designation	HEAVY DUTY SWITCH			
type of electrical connection	MECHANICAL LUGS			
Mechanical Design				
design of the housing	TYPE 4X			
design of the actuating element	SINGLE THROW			
material	FIBERGLASS REINFORCED POLYESTER			
General product approval				
certificate of suitability	UL98			

last modified:

9/16/2021 🖸