

# Product data sheet

Specifications



## Power base, TeSys Ultra, 12 A, screw clamps control

LUB12

Product availability: Stock - Normally stocked in distribution facility

Price\*: 246.00 USD

### Main

Range	TeSys
Product Name	TeSys Ultra
Device Short Name	LUB
Product Or Component Type	Non reversing power base
Device Application	Motor control Motor protection
Poles Description	3P
Suitability For Isolation	Yes
[Ue] Rated Operational Voltage	690 V AC power circuit
Network Frequency	40...60 Hz
[Ith] Conventional Free Air Thermal Current	12 A
[Ie] Rated Operational Current	12 A <= 440 V 12 A 500 V 9 A 690 V
Utilisation Category	AC-43 AC-44 AC-41
[Ics] Rated Service Breaking Capacity	50 kA 230 V 50 kA 440 V 10 kA 500 V 4 kA 690 V
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	Linked contacts 1 NO + 1 NC) IEC 60947-4-1 Mirror contact 1 NC) IEC 60947-1
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz 24 V DC 48...72 V AC 50/60 Hz 48...72 V DC 110...240 V AC 50/60 Hz 110...220 V DC

### Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Typical Current Consumption</b>	<p>130 mA 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>140 mA 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>150 mA 24 V DC I maximum while closing with LUCM</p> <p>280 mA 110...220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 110...240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 48...72 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 48...72 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA 110...220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA 110...240 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA 48...72 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA 48...72 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>60 mA 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>70 mA 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>70 mA 24 V DC I rms sealed with LUCM</p>
<b>Heat Dissipation</b>	<p>2 W control circuit with LUCA, LUCB, LUCC, LUCD</p> <p>1.7 W control circuit with LUCM</p>
<b>Safety Reliability Level</b>	<p>B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1</p> <p>B10d = 2000000 cycles contactor with mechanical load EN/ISO 13849-1</p>
<b>Operating Time</b>	<p>35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM control circuit</p> <p>50 ms &gt;= 72 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>60 ms 48 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>70 ms 24 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>75 ms closing with LUCM control circuit</p>
<b>Mechanical Durability</b>	15 Mcycles
<b>Maximum Operating Rate</b>	3600 cyc/h
<b>Product Certifications</b>	<p>CE</p> <p>UL</p> <p>CSA</p> <p>CCC</p> <p>EAC</p> <p>ASEFA</p> <p>ATEX</p> <p>Marine</p>
<b>Standards</b>	<p>EN 60947-6-2</p> <p>IEC 60947-6-2</p> <p>UL 60947-4-1, with phase barrier</p> <p>CSA C22.2 No 60947-4-1, with phase barrier</p>
<b>[Ui] Rated Insulation Voltage</b>	<p>690 V IEC 60947-6-2 3)</p> <p>600 V UL 60947-4-1</p> <p>600 V CSA C22.2 No 60947-4-1</p>
<b>[Uimp] Rated Impulse Withstand Voltage</b>	6 kVIEC 60947-6-2
<b>Safe Separation Of Circuit</b>	<p>400 V SELV between the control and auxiliary circuits IEC 60947-1 appendix N</p> <p>400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1 appendix N</p>
<b>Fixing Mode</b>	<p>Clipped (DIN rail)</p> <p>Screw-fixed (plate)</p>
<b>Connections - Terminals</b>	<p>Control circuit screw clamp terminals 1 0.00...0.00 in<sup>2</sup> (0.34...1.5 mm<sup>2</sup>) flexible with cable end</p> <p>Control circuit screw clamp terminals 1 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) flexible without cable end</p> <p>Control circuit screw clamp terminals 1 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) rigid</p> <p>Control circuit screw clamp terminals 2 0.00...0.00 in<sup>2</sup> (0.34...1.5 mm<sup>2</sup>) flexible with cable end</p> <p>Control circuit screw clamp terminals 2 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) flexible without cable end</p> <p>Control circuit screw clamp terminals 2 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) rigid</p> <p>Power circuit screw clamp terminals 1 0.00...0.02 in<sup>2</sup> (1...10 mm<sup>2</sup>) rigid</p> <p>Power circuit screw clamp terminals 1 0.00...0.01 in<sup>2</sup> (1...6 mm<sup>2</sup>) flexible with cable end</p> <p>Power circuit screw clamp terminals 1 0.00...0.02 in<sup>2</sup> (2.5...10 mm<sup>2</sup>) flexible without cable end</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in<sup>2</sup> (1...6 mm<sup>2</sup>) flexible with cable end</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in<sup>2</sup> (1...6 mm<sup>2</sup>) rigid</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in<sup>2</sup> (1.5...6 mm<sup>2</sup>) flexible without cable end</p>

<b>Tightening Torque</b>	Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) flat 0.20 in (5 mm) Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) Philips no 1 0.20 in (5 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) flat 0.24 in (6 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) Philips No 2 0.24 in (6 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) pozidriv No 2 0.24 in (6 mm)
<b>Width</b>	1.77 in (45 mm)
<b>Height</b>	6.06 in (154 mm)
<b>Depth</b>	4.96 in (126 mm)
<b>Net Weight</b>	1.98 lb(US) (0.9 kg)
<b>Compatibility Code</b>	LUB

## Environment

<b>Ip Degree Of Protection</b>	IP20 IEC 60947-1 front panel and wired terminals) IP20 IEC 60947-1 other faces) IP40 IEC 60947-1 front panel outside connection zone)
<b>Protective Treatment</b>	TH IEC 60068
<b>Ambient Air Temperature For Operation</b>	-13...140 °F (-25...60 °C) with LUCM -13...158 °F (-25...70 °C) with LUCA, LUCB, LUCC, LUCD
<b>Ambient Air Temperature For Storage</b>	-40...185 °F (-40...85 °C)
<b>Fire Resistance</b>	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
<b>Operating Altitude</b>	6561.68 ft (2000 m)
<b>Shock Resistance</b>	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27
<b>Vibration Resistance</b>	2 gn 5...300 Hz) power poles open IEC 60068-2-27 4 gn 5...300 Hz) power poles closed IEC 60068-2-27
<b>Resistance To Electrostatic Discharge</b>	8 kV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2
<b>Non-Dissipating Shock Wave</b>	1 kV serial mode 24...240 V AC IEC 60947-6-2 1 kV serial mode 48...220 V DC IEC 60947-6-2 2 kV common mode 24...240 V AC IEC 60947-6-2 2 kV common mode 48...220 V DC IEC 60947-6-2
<b>Resistance To Fast Transients</b>	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
<b>Resistance To Radiated Fields</b>	9.14 V/m (10 V/m) 3 IEC 61000-4-3
<b>Immunity To Radioelectric Fields</b>	10 V IEC 61000-4-6
<b>Immunity To Microbreaks</b>	3 ms control circuit
<b>Immunity To Voltage Dips</b>	70 % / 500 ms IEC 61000-4-11

## Ordering and shipping details

<b>Category</b>	US10I1122396
<b>Discount Schedule</b>	0111
<b>Gtin</b>	3389110362770
<b>Returnability</b>	Yes
<b>Country Of Origin</b>	FR

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1

<b>Package 1 Height</b>	2.05 in (5.200 cm)
<b>Package 1 Width</b>	5.31 in (13.500 cm)
<b>Package 1 Length</b>	6.69 in (17.000 cm)
<b>Package 1 Weight</b>	29.70 oz (842.000 g)
<b>Unit Type Of Package 2</b>	S02
<b>Number Of Units In Package 2</b>	10
<b>Package 2 Height</b>	5.91 in (15.000 cm)
<b>Package 2 Width</b>	11.81 in (30.000 cm)
<b>Package 2 Length</b>	15.75 in (40.000 cm)
<b>Package 2 Weight</b>	19.18 lb(US) (8.698 kg)
<b>Unit Type Of Package 3</b>	P06
<b>Number Of Units In Package 3</b>	160
<b>Package 3 Height</b>	29.53 in (75.000 cm)
<b>Package 3 Width</b>	23.62 in (60.000 cm)
<b>Package 3 Length</b>	31.50 in (80.000 cm)
<b>Package 3 Weight</b>	325.55 lb(US) (147.668 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Mercury Free

 Rohs Exemption Information Yes

 Pvc Free

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)