Specifications



() Discontinued

## TeSys F - contactor coil - LX1FG -220...230 V AC 50 Hz - 265...277 V AC 60 Hz

LX1FG220

Discontinued on: 18-Nov-2021

#### Main

| Range                        | TeSys                                  |  |
|------------------------------|--|--|
| product or component type    | Contactor coil                         |  |
| Device short name            | LX1FG                                  |  |
| Range compatibility          | TeSys TeSys F LC1F contactor           |  |
| Product compatibility        | LC1F185<br>LC1F225                     |  |
| Control circuit type         | AC at 50/60 Hz                         |  |
| [Uc] control circuit voltage | 220230 V AC 50 Hz<br>265277 V AC 60 Hz |  |
| Inductance of closed circuit | 2.59 H                                 |  |
| Average resistance           | 16.5 Ohm at 20 °C                      |  |
| Operating time               | 2035 ms closing<br>715 ms opening      |  |
| Mechanical durability        | 10 Mcycles                             |  |
| Maximum operating rate       | 2400 cyc/h 55 °C                       |  |
|                              |  |  |

## Complementary

| Coil technology                 | Without built-in suppressor module   |
|---------------------------------|--|
| Control circuit voltage limits  | Drop-out: 0.350.55 Uc 50/60 Hz (at 55 °C)<br>Operational: 0.851.1 Uc 50/60 Hz (at 55 °C) |
| Inrush power in VA              | 805 VA 50 Hz cos phi 0.3 (at 20 °C)<br>970 VA 60 Hz cos phi 0.3 (at 20 °C)               |
| Hold-in power consumption in VA | 55 VA 50 Hz cos phi 0.3 (at 20 °C)<br>66 VA 60 Hz cos phi 0.3 (at 20 °C)                 |
| Heat dissipation                | 1824 W at 50/60 Hz   |

### Environment

| Ambient air temperature for operation | -555 °C |
|---------------------------------------|---------|
| net weight                            | 0.55 kg |

## **Packing Units**

| Unit Type of Package 1       | PCE  |
|------------------------------|------|
| Number of Units in Package 1 | 1    |
| Package 1 Height             | 7 cm |

| Package 1 Width  | 8 cm  |
|------------------|-------|
| Package 1 Length | 16 cm |
| Package 1 Weight | 545 g |

# **Contractual warranty**

Warranty

18 months

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

|      | Reach Free Of Svhc         |   |
|------|----------------------------|---|
|      | Toxic Heavy Metal Free     |   |
|      | Mercury Free               |   |
|      | Rohs Exemption Information | Yes   |
|      |                            |   |
| Rea  | ch Regulation              | REACh Declaration   |
| Eu f | Rohs Directive             | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration |
| Chir | na Rohs Regulation         | China RoHS declaration  |