



Metallic mounting plate for PLA enclosure H12150xW1000mm

NSYPMM1210

Main

Range	Thalassa	
Accessory / separate part categor	Mounting accessory	
Product or component type	Mounting plate	
Device application	Multi-purpose	
Enclosure nominal dimensions	s -	
Mounting location	Step slide Back inserts	
Mounting plate description	Plain	
Range compatibility	Thalassa Thalassa PLA	
Device composition	1 mounting plate	
Material	Galvanised steel	

Complementary

Fixing mode	By screws - screw type M8 - on back inserts location
Permanent permissible load	150 kg
Height	Nominal: 1250 mm Real: 1140 mm
Width	Nominal: 1000 mm Real: 875 mm
Depth	Real : 125 mm
Thickness	2.5 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	88.000 cm
Package 1 Length	112.000 cm
Package 1 Weight	20.203 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	45.000 cm
Package 2 Width	100.000 cm

Package 2 Length	120.000 cm
Package 2 Weight	417.341 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations