

# Product data sheet

Specifications



## Spacial SF enclosure without mounting plate - assembled - 2000x1200x400 mm

NSYSF2012402D

⚠ To be discontinued on: Sep 30, 2024

⚠ To be discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 2,017.51 USD

### Main

|                           |   |
|---------------------------|---|
| Range                     | Spacial   |
| Extended range            | Spacial SF  |
| Application               | Multi-purpose   |
| Product or Component Type | Suitable enclosure  |
| Enclosure nominal height  | 78.7 in (2000 mm)   |
| Enclosure nominal width   | 47.2 in (1200 mm)   |
| Enclosure nominal depth   | 15.7 in (400 mm)  |
| enclosure mounting        | Floor-standing  |
| Device composition        | 2 sliding rails<br>4 mounting plate bracket<br>1 structure<br>1 rear panel<br>1 roof<br>2 door<br>1 locking system with handle<br>1 blocking system left door |

### Complementary

|                             |  |
|-----------------------------|--|
| structure type              | Perforated structure with a pitch of 25 mm<br>Panels and doors built into the structure<br>Formed from a single section<br>Vertical uprights joined with top and bottom frames |
| Door opening side           | Left 120 °)<br>Right 120 °)  |
| Door type                   | Solid front  |
| Mounting plate description  | Without mounting plate   |
| Type of gland plate         | Without gland plate  |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert front right door   |
| Number of doors             | Front face 2   |
| accessibility for operation | Rear<br>Sides of enclosure<br>Front  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                        |   |
|------------------------|---|
| <b>Removable parts</b> | Door by screws hinge<br>Mounting plate by screws mounting plate bracket<br>Rear panel by screws<br>Roof by screws<br>Mounting plate bracket by screws<br>Sliding rail by screws |
| <b>Material</b>        | Frame galvanised steel<br>Uprights galvanised steel<br>Door sheet steel<br>Panels sheet steel<br>Hinge zamak<br>Handle polyamide 6 with 30 % fibre glass                        |
| <b>Surface finish</b>  | epoxy-polyester powder  |
| <b>color</b>           | Enclosure Gray RAL 7035<br>Handle Black RAL 9005  |
| <b>Net Weight</b>      | 282.2 lb(US) (128 kg)   |

## Environment

|                                  |                |
|----------------------------------|----------------|
| <b>Standards</b>                 | IEC 62208      |
| <b>NEMA Degree of Protection</b> | NEMA 3R/12     |
| <b>IP degree of protection</b>   | IP55 IEC 60529 |
| <b>IK degree of protection</b>   | IK10 IEC 62262 |

## Ordering and shipping details

|                          |               |
|--------------------------|---------------|
| <b>Category</b>          | US10ES180035  |
| <b>Discount Schedule</b> | 0ES1          |
| <b>GTIN</b>              | 3606485118437 |
| <b>Returnability</b>     | No            |
| <b>Country of origin</b> | ES            |

## Packing Units

|                                     |                         |
|-------------------------------------|-------------------------|
| <b>Unit Type of Package 1</b>       | PCE                     |
| <b>Number of Units in Package 1</b> | 1                       |
| <b>Package 1 Height</b>             | 19.3 in (49.0 cm)       |
| <b>Package 1 Width</b>              | 49.02 in (124.5 cm)     |
| <b>Package 1 Length</b>             | 83.9 in (213.0 cm)      |
| <b>Package 1 Weight</b>             | 284.4 lb(US) (129.0 kg) |
| <b>Unit Type of Package 2</b>       | PAL                     |
| <b>Number of Units in Package 2</b> | 2                       |
| <b>Package 2 Height</b>             | 83.9 in (213.0 cm)      |
| <b>Package 2 Width</b>              | 49.2 in (125.0 cm)      |
| <b>Package 2 Length</b>             | 38.6 in (98.0 cm)       |
| <b>Package 2 Weight</b>             | 568.8 lb(US) (258.0 kg) |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations