



PRODUCT-DETAILS

OVR T2 1N 40-150 P TS U

Surge Protective Device



General Information	
Extended Product Type	OVR T2 1N 40-150 P TS U
Product ID	2CTB802342R2100
EAN	3660308519252
Catalog Description	Surge Protective Device
Long Description	OVR T2 1N 40-150 P TS U Surge Protective Device

Technical	
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U_r)	120 V AC
Nominal AC Voltage of the System (U_o)	120 V
Voltage Protection Level (U_p)	1.1 kV (L-N) 1.1 kV (N-PE) 1.1 kV
Maximum Continuous Operating Voltage (U_c)	(L-PE) 175 V
Rated Service Short-Circuit Breaking	100 kA

Capacity (I _{cs})	
Discharge Current	Nominal (8 / 20 μs) 20 kA I (max, 8 / 20 μs) 40 kA
Short Circuit Withstand I _{cc}	100 kA
Arrester Class	II
Number of Protected Poles	2
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	2P
Number of Conductors	2
Position of Neutral Terminals	Right
Transmission Standard	Optic
Version	Plug-in
Mounting Type	DIN-Rail
Options Provided	Residential, commercial building.
Auxiliary Circuit Load	Minimum 12Vdc - 10mA Maximum 250Vac - 1A
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	2 modular spacing

Material Compliance

RoHS Information	9AKK108466A4967
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20220610
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

Technical UL/CSA

Maximum Continuous Operating Voltage UL/CSA (MCOV)	(L-PE) 175 V (L-L) - V (L-N) 175 V (N-PE) 175 V
Maximum Operating Voltage UL/CSA	175 V
Short-Circuit Current Rating (SCCR)	200 kA
Type of Low Voltage Distribution System UL/CSA	Single Phase

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35.6 mm
Product Net Height	98.5 mm
Product Net Depth / Length	64.8 mm
Product Net Weight	0.24 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	270 g

Certificates and Declarations

Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4967
UL Certificate	2CTC432010G1701

Installation

Instructions and Manuals	2CTC432094M1701
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CTC432173D1701
Mechanical Drawings	2CTC800020F3000.pdf 2CTC800020F3001.dxf 2CTC800020F3002.stp 2CTC800020F3003.igs

External Classifications and Standards

ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363090
UNSPSC	39121610
eClass	V11.0 : 27130805
IDEA Granular Category Code (IGCC)	4906 >> Surge suppressers
Object Classification Code	141DBC
Standards	UL 1449 Ed3

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II



360