

# Product data sheet

Specifications



Load center interior, QO, mounting base, 3 phase, 24 spaces, 200A main lugs, OEM, neutral busbar

QON324L200I

⚠ Discontinued on: May 12, 2023

⚠ Discontinued

## Main

Marketing Trade Name	QO
Product Type	Mounting base

## Complementary

Load Center Type	Main lugs
Rated Current	200 A
Number Of Spaces	24
Max Short Circuit Current Rating	10 kA
Maximum Number Of Single Pole Circuits	24
Maximum Number Of Tandem Breakers	0
Number Of Phases	3 phases 4 wires
Wire Size	AWG 4...300 kcmil copper or aluminum
Height	10.6 in (270 mm)
Width	14.1 in (359 mm)
Depth	3.1 in (79 mm)

## Environment

Ambient Air Temperature For Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL listed

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.10 in (5.334 cm)
Package 1 Width	10.60 in (26.924 cm)
Package 1 Length	18.80 in (47.752 cm)
Package 1 Weight	12.00 lb(US) (5.443 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations