



Figure similar

SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. FACTORY INSTALLED MAIN BREAKER WITH 24 1-INCH SPACES ALLOWING MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A) 22KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE3R ENCLOSURE FOR OUTDOOR USE. REPLACED BY SNW2424B1125. AVAILABLE 4/1/2020

| General technical data                                       |              |
|--|--------------|
| configuration of the busbars                                 | 125 A        |
| fastening method   | Surface      |
| phase number   | 1            |
| suitability for operation                                    | Residential  |
| Electricity  |              |
| ampacity   | 125 A        |
| ampacity minimum   | 125 A        |
| voltage between phase and Ground (GND) rated value           | 120 V        |
| voltage between phase and phase rated value                  | 240 V        |
| Switching capacity   |              |
| switching capacity current according to EN 60898 rated value | 22000 A      |
| Model  |              |
| product brand name   | Siemens      |
| product sub brand name                                       | Load Centers |
| Mechanical Design  |              |
| number of modular width units for installation width         | 24           |

last modified:

6/18/2021

