Specifications



① Discontinued

## universal automation Wifi Interface -IP20 - with RJ45 and USB connectors

TCSEGWB13FA0

- () Discontinued on: Dec 2, 2020
- (!) End-of-service on: Dec 31, 2020

# Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

| Accessory / Separate Part<br>Categor     | Communication accessory   |  |
|--|---|--|
| Accessory / Separate Part Type           | Wireless access point   |  |
| Accessory / Separate Part<br>Destination | Smart phone<br>Phablet<br>Variable speed drive<br>PC<br>Tablet<br>PLC |  |

### Complementary

| ontary            |   |
|-------------------|---|
| ty Modice         | M251  |
| Altivar           | rocess ATV600   |
| Modico            | M580  |
| Altivar           | rocess ATV900   |
| Battery           |   |
| USB c             | le  |
| Power             | daptor  |
| Ethern            | cable   |
| Quick             | art guide   |
| Autom             | ic detection of Schneider-Electric products and other devices on Ethernet |
| Femal             | RJ45 automatic negotiation of 10/100 Mbit/s                               |
| Micro             | SB type A female  |
| ort Protocol DHCP |   |
| PPPoE             | Point-to-Point Protocol over Ethernet)                                    |
| Ethern            | TCP/IP  |
| ICMP              |   |
| CSMA              | Ä   |
| CSMA              | D   |
| Windo             | \$7   |
| Mac iC            |   |
| Androi            |   |
| Windo             | s XP  |
| Windo             | \$ 8  |
| Windo             | s Vista   |
| ents Google       | Chrome  |
| Micros            | t internet explorer   |
| Apple             | afari   |
| Firefox           |   |
| Recha             | eable internal battery  |
| Firefox           |   |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Net Weight

for scan status 1 LED 0.77 lb(US) (0.35 kg)

### Environment

| Ip Degree Of Protection                  | IP20  |
|--|---|
| Ambient Air Temperature For<br>Operation | 32104 °F (040 °C)   |
| Ambient Air Temperature For<br>Storage   | -40158 °F (-4070 °C)  |
| Relative Humidity                        | 1090 % operation, without condensation IEC 60068-2-3 590 % storage, without condensation IEC 60068-2-3  |
| Standards                                | IEEE 802.11g<br>IEEE 802.11n<br>IEEE 802.1x<br>IEEE 802.3<br>IEEE 802.3x<br>IEEE 802.3u<br>IEEE 802.11b |
| Product Certifications                   | FCC<br>CE   |

for battery status 1 LED (green, orange and red)

for Ethernet port activity 1 LED for wireless function status 1 LED

# Ordering and shipping details

| Category          | US1CP4E22205   |
|-------------------|----------------|
| Discount Schedule | CP4E           |
| Gtin              | 00785901691730 |
| Returnability     | No             |
| Country Of Origin | US             |

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >


Guide to assess a product's sustainability >

### Well-being performance

| Mercury Free               |   |
|----------------------------|---|
| Rohs Exemption Information | Yes   |
| Eu Rohs Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration |
| China Rohs Regulation      | China RoHS declaration  |

#### Presentation

#### Presentation



| Item | Description    |
|------|----------------|
| (1)  | Power switch   |
| (2)  | Micro USB port |
| (3)  | Reset button   |
| (4)  | Ethernet port  |