

Siemens Low Voltage's Multi-Family Metering Line of PAK Metering: EUSERC as part of the PAK Metering: EUSERC Group. Type: UNI-PAK Features: EUSERC COMPLIANT Appn: GARDEN - STYLE Std: UL-50,67,414 V. Rating: 120/240V A. Rating: 600A Phase: 1PH Size: 9.00 x 45.07 x 39.630 No. Of Cutouts: 18 Cutout Size: 1 x (1/2,3/4,1,1-1/4"), 12 x (2-1/2,2,1-1/2,1-1/4,1"), 2 x (4,3-1/2,3,2-1/2,2"), 1X1/2",2X4" Cable Entry: TOP OR BOTTOM FEED Terminal: 3X2 STUDS. Insulated. Appn.: Wall Mounted. Enclosure: RING

General technical data	
cable entry type	TOP OR BOTTOM FEED
fastening method	WALL MOUNTED
suitability for operation	GARDEN-STYLE
Electricity	
ampacity	600 A
Model	
product brand name	Siemens
product type designation	UNI-PAK
special product feature	EUSERC COMPLIANT
Mechanical Design	
design of the terminal strip	3X2 STUDS
General product approval	
certificate of suitability	UL-50;67;414

last modified:

5/9/2023 

