



PRODUCT-DETAILS

XT1N 125 TMF 30-500 3p F F UL/CSA

XT1N 125 TMF 30-500 3p F F UL/CSA



General Information	
Extended Product Type	XT1N 125 TMF 30-500 3p F F UL/CSA
Product ID	1SDA074637R1
EAN	8015644785048
Catalog Description	XT1N 125 TMF 30-500 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT1N 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 30-500 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2347
Environmental Product Declaration - EPD	9AKK108468A1890
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 55.9 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	e2200995-5d7a-4972-b5fb-894afbae3851 Italy (IT)
Simplified SCIP	5c2c7f27-9591-495e-acd3-dcf109a16c48 Germany (DE) a83373d9-ed9b-4cb6-a034-9348a186b0ba Netherlands (NL) 24925faa-75b1-41b3-aafe-3e14a0c8f5b3 Portugal (PT) 44e8e08a-acdb-449e-a630-00f51905483f Bulgaria (BG) 0c3841c0-ae66-4971-8424-0a05d39282c4 Sweden (SE) 8d7fb306-399e-45ef-8170-ef3b8cc75e87 Poland (PL) b63847d5-b49e-4775-8186-ec0248989b7f France (FR) e0531326-f6d9-4337-acd9-3a297788620a Sweden (SE) c18f3686-94bf-464b-86a7-ff2750ab61c7 Germany (DE) fc2548e9-2d02-408a-9599-621a6484e447 Estonia (EE) 794a96dc-e0d7-4a43-9b0a-c6955f0ed120 Germany (DE) 816d96ea-95dc-4d46-af30-271c3dc407af Denmark (DK) 09f1ccc3-9158-45af-bfa2-2d1503647cfe Germany (DE) 4152072e-fc05-4795-9ca5-7c4d66e3a797 Croatia (HR) 16da7102-cce7-464d-82c7-f2ed10eb9a2f Czech Republic (CZ) adad12db-287b-4a9c-af02-5ee19dd15c03 Poland (PL) 4f4bd9ef-29c3-4ed9-bce6-664db60a0bf9 Norway (NO) 4f8b0f85-96a2-4fed-8e0f-b7e1a567898a Finland (FI) b3c472af-113b-4dcc-ba19-8849f626e96f Poland (PL) 1b6b3328-5bab-47a4-85e7-76e08e961871 Netherlands (NL) 3b0025d4-6c1e-4918-8aef-b31e7ef865a8 Netherlands (NL) 199727dc-3a10-4a17-915f-52fa5300d1b6 Germany (DE) 1862f452-d1c2-4290-b867-f000d5100152 France (FR) 31c00e45-ab83-493d-a668-c4224e7f0172 Netherlands (NL) b0f29119-6bc9-4469-9395-5c716a7fb566 Spain (ES) 688a0ad7-66f0-4778-bba8-2868777ad4eb Netherlands (NL) a4f1514f-ec1e-4d53-8286-415acac5fba5 Greece (GR)

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT1NU3030AFF000XXX
EAN	8015644785048
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm
Product Net Weight	1.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	8015644785048

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable for Product Class	SACE Tmax XT
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Technical

Connecting Capacity Main Circuit	Busbar 45.5 ... 80 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 1.8 W
Rated Current (I _n)	30 A
Rated Instantaneous Short-Circuit Current Setting (I _i)	500 A
Rated Operational Voltage	600Y/347 V AC 500 V DC
Rated Uninterrupted Current (I _u)	125 A
Rated Voltage (U _r)	600Y/347 V
Recommended Screw Driver	Main Circuit M6
Release	TMF
Release Type	TM
Setting Range	30 A
Short-Circuit Performance Level	N
Standards	UL489
Sub-type	XT1

Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA (480 V AC) 25 kA (600Y / 347 V AC) 18 kA (250 V DC) 2 Poles in Series 35 kA (500 V DC) 4 Poles in Series Kind 35 kA
-----------------------------------	--

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3905
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5532
UL Certificate	1SDL000163R0111
VDE Certificate	No certification needed
Dimension Diagram	1SDH000719R0100
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0003

External Classifications and Standards

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

