

# Product data sheet

Specifications



## Pilot light, Harmony XVL, plastic, red, 12mm, covered LED, 12V DC

XVLA324

Product availability: Stock - Normally stocked in distribution facility

Price\*: 52.00 USD

### Main

Range Of Product	Harmony XVL
Product Or Component Type	LED pilot light with integral lens cap
Component Name	XVL
Mounting Diamete	0.47 in (12 mm)
Light Source	Covered LED
Light Block Colour	Red
Protection Type	Built-in by diode Integral ballast resistor
[Us] Rated Supply Voltage	12 V
Ip Degree Of Protection	IP65 IEC 60529 with seal XVLZ912) IP65 NF C 20-010 with seal XVLZ912) IP40 IEC 60529 IP40 NF C 20-010

### Complementary

Supply Circuit Type	DC
Connections - Terminals	Threaded connector 1 x 0.2...1 x 1.5 mm <sup>2</sup>
Current Consumption	18 mA
[Ui] Rated Insulation Voltage	50 V IEC 60947-1
Bulb Lifespan	100000 h
Nominal Voltage Limit	0.8...1.1 Un
Terminals Description Iso N°1	(X1-X2)PL
Height	0.63 in (16 mm)
Width	0.63 in (16 mm)
Depth	2.01 in (51 mm)
Net Weight	0.02 lb(US) (0.007 kg)

### Environment

Product Certifications	CSA UL
Protective Treatment	TC
Ambient Air Temperature For Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Overvoltage Category	Class 3 IEC 60536 Class 3 NF C 20-030
----------------------	--

## Ordering and shipping details

---

Category	US10CS222460
Discount Schedule	0CS2
Gtin	3389110651621
Returnability	Yes
Country Of Origin	US

## Packing Units

---

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.59 in (1.5 cm)
Package 1 Width	0.59 in (1.5 cm)
Package 1 Length	1.97 in (5.0 cm)
Package 1 Weight	0.25 oz (7.0 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	1.18 in (3.0 cm)
Package 2 Width	3.94 in (10.0 cm)
Package 2 Length	5.12 in (13.0 cm)
Package 2 Weight	2.65 oz (75.0 g)
Unit Type Of Package 3	S01
Number Of Units In Package 3	100
Package 3 Height	5.91 in (15.0 cm)
Package 3 Width	5.91 in (15.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	31.25 oz (886.0 g)

## Contractual warranty

---

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Mercury Free

 Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile No need of specific recycling operations


California Proposition 65 WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Dimensions Drawings

LED Pilot Light

---

Dimensions



(1) Threaded connector


e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

Mounting and Clearance

LED Pilot Light

---

Panel Drilling



Ø min		G min		H min	
mm	in.	mm	in.	mm	in.
12.2	0.48	16.5	0.65	16.5	0.65