







## Expansion I/O

**Stock Note:** Shaded models are normally stocked.

No. of I/O points/Appearance	Inputs	4 inputs	Outputs	4 outputs	Model
8 I/O 	100 to 240 VAC (isolated)		Relays		ZEN-8EAR
	24 VDC (isolated)		Transistors		ZEN-8EDR ZEN-8EDT
4 inputs 	100 to 240 VAC (isolated)		—	—	ZEN-4EA
	24 VDC (isolated)		ZEN-4ED		
4 outputs 	—	—	Relays	4 outputs	ZEN-4ER


## Optional Accessories

**Stock Note:** Shaded models are normally stocked.

Name and appearance	Functions	Model
Memory Cassette 	EEPROM Used to save and copy programs	ZEN-ME01
Battery Unit 	Uses a battery to back up programs and data. Mount a Battery Unit if the loss of calendar, clock, holding bit, holding timer, and counter present values will cause problems in systems with long power interruptions. (Battery life: 10 years minimum)	ZEN-BAT01
Personal Computer Connecting Cable 	Connects the computer and ZEN when the ZEN Support Software is used. (Cable length: 2 m)	ZEN-CIF01

## Support Software

**Stock Note:** Shaded models are normally stocked.

Name and appearance	Functions	Model
ZEN Support Software 	Runs on Windows 95, 98, ME, 2000, XP, or NT4.0 Service Pack 3 (CD-ROM) Used for offline programming, all parameter settings, program transfers, and printing.	ZEN-SOFT01-V_

## Manuals

Product	Description	Model
Operation Manual	ZEN Programmable Relay Operation Manual	Z183
Operation Manual	ZEN Support Software Operation Manual	Z184